

Foreword

NEARLY TWENTY YEARS after the first ideas for L^AT_EX_{2 ϵ} emerged, the use of L^AT_EX to produce high-quality technical documents shows no sign of waning. Indeed, over the past 5 or so years there has been if anything an *upturn* in interest in using L^AT_EX. Better editors, faster computers and the range of powerful L^AT_EX packages have all contributed to this increased uptake.

For the new user, this vibrancy can appear intimidating. The range of packages available for use with L^AT_EX is vast, and it is not always obvious which is the ‘best of breed.’ What new users need therefore is a guide not just to the basics of the L^AT_EX approach, but also help in navigating this ecosystem so that they can produce the documents they need as rapidly as possible.

Creating well-designed documents is about more than the technical detail of any typesetting system, and so as well as learning L^AT_EX it is also necessary to understand the wider ideas of good writing and good design if one is to create truly ‘beautiful’ material.

In *L^AT_EX and Friends*, Marc van Dongen provides an integrated solution to these inter-related requirements. Treating the presentation of beautiful documents as the key aim of the reader, it offers advice on good practice (both in L^AT_EX terms and beyond) in the relevant context for the beginner. It also avoids the problem seen in many texts, which fall short in supporting the transition from beginner to advanced user. Thus while new L^AT_EX users will find the information they need here, so will more established users, making this not only a beginners’ guide but also a reference manual for day-to-day L^AT_EX users.

Joseph Wright

Contents

Foreword	v
Preface	xxiii
Book Outline	xxv
Acknowledgements	xxvii
I Basics	1
1 Introduction to L^AT_EX	3
1.1 Pros and Cons	4
1.2 Basics	6
1.2.1 The T _E X Processors	6
1.2.2 From tex to dvi and Friends	6
1.2.3 The Name of the Game	8
1.2.4 Staying in Sync	8
1.2.5 Writing a L ^A T _E X Input Document	8
1.2.6 The Abstract	11
1.2.7 Spaces, Comments, and Paragraphs	12
1.3 Document Hierarchy	12
1.3.1 Minor Document Divisions	13
1.3.2 Major Document Divisions	14
1.3.3 The Appendix	15
1.4 Document Management	15
1.5 Labels and Cross-references	16
1.6 Controlling the Style of References	18
1.7 The Bibliography	19
1.7.1 The bibtex Program	23
1.7.2 The biblatex Package	25
1.7.3 End-of-Chapter Bibliographies	27
1.7.4 Classified Bibliographies	28
1.8 Table of Contents and Lists of Things	29
1.8.1 Controlling the Table of Contents	30
1.8.2 Controlling the Sectional Unit Numbering	30
1.8.3 Indexes and Glossaries	30
1.9 Class Files	32

1.10	Packages	34
1.11	Useful Classes and Packages	35
1.12	Errors and Troubleshooting	35
II Basic Typesetting		39
2	Running Text	41
2.1	Special Characters	41
2.1.1	Tieing Text	41
2.1.2	Grouping	43
2.2	Diacritics	44
2.3	Ligatures	44
2.4	Quotation Marks	45
2.5	Dashes	46
2.6	Full Stops	46
2.7	Ellipsis	47
2.8	Emphasis	48
2.9	Borderline Punctuation	48
2.10	Footnotes and Marginal Notes	48
2.11	Displayed Quotations and Verses	49
2.12	Line Breaks	49
2.13	Controlling the Size	50
2.14	Seriffed and Sans Serif Typefaces	51
2.15	Small Caps Letters	52
2.16	Controlling the Type Style	53
2.17	Abbreviations	53
2.17.1	Initialisms	53
2.17.2	Acronyms	54
2.17.3	Shortenings	54
2.17.4	Introducing Abbreviations	55
2.17.5	British and American Spelling	55
2.17.6	Latin Abbreviations	56
2.17.7	Units	56
2.18	Phantom Text	57
2.19	Alignment	58
2.19.1	Centred Text	58
2.19.2	Flushed/Ragged Text	58
2.19.3	Basic tabular Constructs	58
2.19.4	The booktabs Package	61
2.19.5	Advanced tabular Constructs	61
2.19.6	The tabbing Environment	64
2.20	Language Related Issues	64
2.20.1	Hyphenation	64
2.20.2	Foreign Languages	65
2.20.3	Spell-Checking	66
3	Lists	67
3.1	Unordered Lists	67

3.2	Ordered Lists	68
3.3	The enumerate Package	69
3.4	Description Lists	69
3.5	Making your Own Lists	70
III Tables, Diagrams, and Data Plots		73
4	Presenting External Pictures	75
4.1	The figure Environment	75
4.2	Special Packages	76
4.2.1	Floats	76
4.2.2	Legends	77
4.3	External Picture Files	77
4.4	The graphicx Package	77
4.5	Setting Default Key Values	78
4.6	Setting a Search Path	79
4.7	Graphics Extensions	79
5	Presenting Diagrams	81
5.1	Why Specify your Diagrams?	81
5.2	The tikzpicture Environment	82
5.3	The \tikz Command	82
5.4	Grids	83
5.5	Paths	83
5.6	Coordinate Labels	84
5.7	Extending Paths	85
5.8	Actions on Paths	88
5.8.1	Colour	89
5.8.2	Drawing the Path	91
5.8.3	Line Width	91
5.8.4	Dash Patterns	91
5.8.5	Predefined Styles	92
5.8.6	Line Cap and Join	92
5.8.7	Arrows	93
5.8.8	Filling a Path	94
5.8.9	Path Filling Rules	95
5.9	Nodes and Node Labels	96
5.9.1	Predefined Nodes Shapes	97
5.9.2	Node Options	98
5.9.3	Connecting Nodes	99
5.9.4	Special Node Shapes	100
5.10	The spy Library	101
5.11	Trees	101
5.12	Logic Circuits	103
5.13	Commutative Diagrams	104
5.14	Coordinate Systems	105
5.15	Coordinate Calculations	108
5.15.1	Relative and Incremental Coordinates	108

5.15.2	Complex Coordinate Calculations	109
5.16	Options	111
5.17	Styles	111
5.18	Scopes	112
5.19	The <code>\foreach</code> Command	113
5.20	The <code>let</code> Operation	114
5.21	The <code>To Path</code> Operation	115
6	Presenting Data in Tables	117
6.1	Why Use Tables?	117
6.2	Table Taxonomy	117
6.3	Table Anatomy	118
6.4	Table Design	119
6.5	Aligning Columns with Numbers	121
6.5.1	Aligning Columns by Hand	122
6.5.2	The <code>dcolumn</code> Package	123
6.5.3	The <code>siunitx</code> Package	124
6.6	The <code>table</code> Environment	124
6.7	Wide Tables	125
6.8	Multi-page Tables	125
6.9	Databases and Spreadsheets	126
7	Presenting Data with Plots	129
7.1	The Purpose of Data Plots	129
7.2	Pie Charts	129
7.3	Introduction to <code>pgfplots</code>	131
7.4	Bar Graphs	132
7.5	Paired Bar Graphs	134
7.6	Component Bar Graphs	135
7.7	Coordinate Systems	136
7.8	Line Graphs	137
7.9	Scatter Plots	139
IV	Mathematics and Algorithms	143
8	Mathematics	145
8.1	The $\mathcal{A}\mathcal{M}\mathcal{S}$ - $\mathcal{L}\mathcal{A}\mathcal{T}\mathcal{E}\mathcal{X}$ Platform	145
8.2	$\mathcal{L}\mathcal{A}\mathcal{T}\mathcal{E}\mathcal{X}$'s Math Modes	146
8.3	Ordinary Math Mode	146
8.4	Subscripts and Superscripts	147
8.5	Greek Letters	147
8.6	Display Math Mode	149
8.6.1	The <code>equation</code> Environment	149
8.6.2	The <code>split</code> Environment	150
8.6.3	The <code>gather</code> Environment	151
8.6.4	The <code>align</code> Environment	151
8.6.5	Interrupting a Display	153
8.6.6	Low-level Alignment Building Blocks	153
8.6.7	The <code>eqnarray</code> Environment	154

8.7	Text in Formulae	154
8.8	Delimiters	154
8.8.1	Scaling Left and Right Delimiters	155
8.8.2	Bars	156
8.8.3	Tuples	157
8.8.4	Floors and Ceilings	158
8.8.5	Delimiter Commands	158
8.9	Fractions	158
8.10	Sums, Products, and Friends	159
8.10.1	Basic Typesetting Commands	159
8.10.2	Overriding Text and Display Style	160
8.10.3	Multi-line Limits	161
8.11	Existing Functions and Operators	161
8.12	Integration and Differentiation	162
8.12.1	Integration	162
8.12.2	Differentiation	164
8.13	Roots	164
8.14	Changing the Style	165
8.15	Symbol Tables	165
8.15.1	Operator Symbols	165
8.15.2	Relation Symbols	166
8.15.3	Arrows	166
8.15.4	Miscellaneous Symbols	167
9	Advanced Mathematics	171
9.1	Declaring New Operators	171
9.2	Managing Content with the cool Package	172
9.3	Arrays and Matrices	172
9.4	Accents, Hats, and Other Decorations	173
9.5	Braces	174
9.6	Case-based Definitions	175
9.7	Function Definitions	175
9.8	Theorems	176
9.8.1	Theorem Taxonomy	176
9.8.2	Styles for Theorem-like Environments	177
9.8.3	Defining Theorem-like Environments	178
9.8.4	Defining Theorem-like Styles	179
9.8.5	Proofs	179
9.9	Mathematical Punctuation	180
9.10	Spacing and Linebreaks	181
9.10.1	Line Breaks	181
9.10.2	Conditions	182
9.10.3	Physical Units	183
9.10.4	Sets	183
9.10.5	More Spacing Commands	184
10	Algorithms and Listings	185
10.1	Presenting Pseudo-Code with algorithm2e	185
10.1.1	Loading algorithm2e	185

10.1.2	Basic Environments	186
10.1.3	Describing Input and Output	187
10.1.4	Conditional Statements	187
10.1.5	The Switch Statement	189
10.1.6	Iterative Statements	190
10.1.7	Comments	191
10.2	The listings Package	192
 V Automation		195
 11 Commands and Environments		197
11.1	Some Terminology	197
11.2	Advantages and Disadvantages	197
11.3	User-defined Commands	199
11.3.1	Defining Commands Without Parameters	199
11.3.2	Defining Commands With Parameters	200
11.3.3	Fragile and Robust Commands	201
11.3.4	Defining Robust Commands	202
11.4	Commands and Parameters	202
11.5	Defining Commands with \TeX	204
11.6	Tweaking Existing Commands with $\backslash\text{let}$	208
11.7	Using More than Nine Parameters	208
11.8	Using Environments	209
 12 Branching		211
12.1	Counters, Switches, and Lengths	211
12.1.1	Counters	211
12.1.2	Switches	212
12.1.3	Lengths	213
12.1.4	Scoping	215
12.2	The ifthen Package	215
12.3	The calc Package	217
12.4	Looping	217
12.5	Tail Recursion	218
 13 Option Parsing		219
13.1	What is a $\langle\text{Key}\rangle=\langle\text{Value}\rangle$ Interface?	219
13.2	Why Use a $\langle\text{Key}\rangle=\langle\text{Value}\rangle$ Interface?	220
13.3	The pgfkeys Package	220
13.4	Providing and Using the Values	220
13.5	Traversing the Key Tree	221
13.6	Executing Keys	222
13.7	Error Handling	222
13.8	Storing Values in Macros	223
13.9	Decisions	223
13.10	Choice Keys	224

VI	Miscellany	225
14	Beamer Presentations	227
14.1	Frames	227
14.2	Modal Presentations	229
14.3	Incremental Presentations	231
14.4	Visual Alerts	233
14.5	Adding Some Style	233
15	Writing Classes and Packages	239
15.1	The Structure of Classes and Packages	239
15.2	Dependencies	239
15.3	Identification	240
15.4	Defining and Parsing the Options	240
15.5	Loading Existing Classes and Packages	241
15.6	Final Configuration	242
16	Using OpenType Fonts	245
16.1	OpenType Font Features	246
16.2	L ^A T _E X Font Selection Mechanism	248
16.3	Overview of Functionality	251
16.4	Inspecting the Font	252
16.5	Current Alternatives	254
16.6	Designing the Font Families	254
16.7	Extracting the Fonts	255
16.8	Font Definition Files	257
16.9	Creating the Font Definition Files	258
16.10	Implementing a Font Package	259
16.10.1	Parsing the Point Size	259
16.10.2	Loading the Font	262
16.10.3	Changing the Features	263
16.11	Using the Fonts	265
17	Using L^AT_EX on Windows	267
17.1	Removing Your Previous Installation	267
17.2	Installing T _E X Live	267
17.2.1	Proxy Configuration	268
17.2.2	Downloading the Installer	268
17.2.3	Running the Installer	268
17.2.4	Minor Configuration	269
17.2.5	Testing the Installation	269
17.3	First Steps with TeXworks	269
17.4	Creating Bibliographies with TeXworks	272
17.4.1	Creating One Single Bibliography	272
17.4.2	Creating Several Bibliographies	272
17.5	Creating Indexes with TeXworks	273
17.6	The L ^A T _E Xmk Typesetting Engine	275
17.7	Bibliography Management with JabRef	275
17.7.1	Installing JabRef	275
17.7.2	Using JabRef	276

17.8	Installing Classes and Packages	278
17.8.1	The \TeX Directory Structure	278
17.8.2	Updating an ls-R Database	279
17.8.3	How kpathsea Finds its Files	280
17.8.4	Installing Packages with tlmgr	281
17.8.5	Installing Packages by Hand	282
18	Using \LaTeX on Unix	285
18.1	Removing Your Previous Installation	285
18.2	Installing \TeX Live	285
18.2.1	Downloading the Installer	286
18.2.2	Running the Installer	286
18.2.3	Setting the Environment Variables	287
18.2.4	Minor Configuration	287
18.2.5	Testing the Installation	289
18.3	First Steps with TeXworks	289
18.4	Creating Bibliographies with TeXworks	291
18.4.1	Creating One Single Bibliography	291
18.4.2	Creating Several Bibliographies	292
18.5	Creating Indexes with TeXworks	293
18.6	The LaTeXmk Typesetting Engine	294
18.7	Bibliography Management with JabRef	295
18.7.1	Installing JabRef	295
18.7.2	Using JabRef	295
18.8	Installing Classes and Packages	296
18.8.1	The \TeX Directory Structure	298
18.8.2	Updating an ls-R Database	298
18.8.3	How kpathsea Finds its Files	300
18.8.4	Installing Packages with tlmgr	301
18.8.5	Installing Packages by Hand	301
	VII References and Bibliography	305
	Typographic Jargon	307
	Bibliography	313
	Acronyms and Abbreviations	319
	Indexes	321
	\LaTeX and TeX Commands	323
	Environments	333
	Classes	335
	Packages	337
	Languages and External Commands	339
	Environment Variables	341

List of Figures

1.1	Typical L ^A T _E X program	9
1.2	Defining comments	12
1.3	Coarse document divisions	14
1.4	Closed fold in folding editor.	15
1.5	Open fold in folding editor.	15
1.6	the Using <code>\includeonly</code> and <code>\include</code> commands . . .	16
1.7	Using <code>\label</code> and <code>\ref</code>	17
1.8	Using <code>\pageref</code>	17
1.9	Using the <code>prettyref</code> package	19
1.10	A minimal bibliography	20
1.11	The <code>\cite</code> command	21
1.12	Using <code>\cite</code> with an optional argument	22
1.13	Including a bibliography	24
1.14	Some B _I B _T E _X entries	24
1.15	Using <code>biblatex</code>	25
1.16	Textual and parenthetical citations	26
1.17	Getting the author and year of a citation	26
1.18	Using <code>biblatex</code> 's citation commands	27
1.19	Including reference lists	30
1.20	Minimal letter	34
2.1	Quotes	45
2.2	Nested quotations	45
2.3	Dashes	47
2.4	Good borderline punctuation	48
2.5	Poor borderline punctuation	48
2.6	Using footnotes	49
2.7	The <code>quote</code> environment	50
2.8	The <code>verse</code> environment	50
2.9	Controlling the size	51
2.10	Finer points of typesetting abbreviations	54
2.11	The <code>\phantom</code> command	57
2.12	The <code>center</code> environment	58
2.13	The <code>flushleft</code> environment	59
2.14	Using the <code>tabular</code> environment	60
2.15	Input of <code>booktabs</code> package	62
2.16	Output of <code>booktabs</code> package	62
2.17	Controlling column widths with an @-expression . . .	63

2.18	The tabbing environment	64
2.19	Advanced tabbing	65
2.20	Using the babel package	65
3.1	The itemize environment	68
3.2	Changing the item label	68
3.3	The enumerate environment	69
3.4	Using the enumerate package	70
3.5	Using the description environment	70
3.6	Lengths that affect list formatting	71
3.7	A user-defined list	72
3.8	A user-defined environment for lists	72
4.1	Using the dpfloat package	77
4.2	Including an external graphics file	78
5.1	Drawing a grid	83
5.2	Creating a path	84
5.3	Cubic spline in tikz	86
5.4	Using a dash pattern	91
5.5	Using a dash phase	91
5.6	Using the miter option	93
5.7	Using the nonzero rule	96
5.8	Using the even odd rule	96
5.9	Nodes and implicit labels	97
5.10	Low-level node control	98
5.11	Node placement	99
5.12	Drawing lines between node shapes	100
5.13	The circle split node style	100
5.14	A node with rectangle style and several parts	101
5.15	Using the spy library	102
5.16	Drawing a tree	102
5.17	Using implicit node labels in trees	102
5.18	Controlling the node style	103
5.19	A tree with a ‘missing’ node	103
5.20	Drawing a half adder with tikz	105
5.21	Input of commutative diagram	106
5.22	Commutative diagram	106
5.23	Using four coordinate systems	107
5.24	Computing the intersection of perpendicular lines	107
5.25	Absolute, relative, and incremental coordinates	108
5.26	Computations with partway modifiers	109
5.27	Computations with partway and distance modifiers	109
5.28	Computations with projection modifiers	109
5.29	Predefining options with the \tikzset command	112
5.30	Using scopes	113
5.31	The \foreach command	113
5.32	Simple to path example	116
5.33	User-defined to path	116

6.1	Components of a demonstration table	118
6.2	Aligning columns with the <code>dcolumn</code> package	124
6.3	Aligning columns with the <code>siunitx</code> package	124
6.4	Creating a table	125
6.5	Using the <code>longtable</code> package	126
7.1	A pie chart	130
7.2	Using the <code>axis</code> environment	131
7.3	Sample output of the <code>axis</code> environment	131
7.4	A bar graph	133
7.5	Creating a bar graph	133
7.6	A paired bar graph	135
7.7	Creating a paired bar graph	135
7.8	A component bar graph	137
7.9	Creating a component bar graph	137
7.10	A line graph	138
7.11	Creating a line graph	139
7.12	A scatter plot	140
7.13	Creating a scatter plot	140
8.1	The <code>equation</code> environment	150
8.2	The <code>split</code> environment	151
8.3	The <code>gather</code> environment	151
8.4	Using the <code>align</code> environment	152
8.5	Output of input in Figure 8.4	152
8.6	The <code>align</code> environment	153
8.7	Output of input in Figure 8.6	153
8.8	Using the <code>\shortintertext</code> command	153
8.9	The <code>aligned</code> environment	154
8.10	Angular delimiters	157
8.11	The <code>\substack</code> command with centred lines	161
8.12	The <code>subarray</code> environment with different alignments	161
8.13	Limit of a log-like function	162
9.1	The <code>array</code> environment	172
9.2	The <code>smallmatrix</code> environment	173
9.3	Typesetting an underbrace	175
9.4	Using the <code>amsthm</code> package	179
9.5	Using the mathematical punctuation commands	181
10.1	Algorithm style	186
10.2	Using <code>algorithm2e</code>	187
10.3	Typesetting conditional statements	189
10.4	Using <code>algorithm2e</code> 's switch statements	190
10.5	Creating a partial listing with the <code>listings</code> package	193
10.6	Listing created from input in Figure 10.5	193
10.7	Setting new defaults with the <code>\lstset</code> command	194
11.1	User-defined commands	201
11.2	A program with user-defined combinators	204

11.3	Using the <code>\expandafter</code> command	207
11.4	Defining commands with default parameters	207
11.5	A sectional unit environment	208
11.6	Accessing parameters by defining commands	209
11.7	Accessing parameters with a nested definition	209
11.8	User-defined environment	210
12.1	Tail recursion	218
14.1	Creating a titlepage with the <code>beamer</code> class	228
14.2	Creating frame titles	228
14.3	Using the <code>beamerarticle</code> package	230
14.4	Using modes	230
14.5	Using the <code>\pause</code> command	232
14.6	Using overlay specifications	233
14.7	Adding visual alerts	233
14.8	Sample output of <code>beamer</code> 's default theme	235
14.9	Sample output of <code>beamer</code> 's <code>Boadilla</code> theme	235
14.10	Sample output of <code>beamer</code> 's <code>Antibes</code> theme	236
14.11	Sample output of <code>beamer</code> 's <code>Goettingen</code> theme	236
14.12	Using a <code>beamer</code> theme	237
15.1	Declaring class options	241
15.2	Loading auxiliary classes and packages	242
16.1	Stylistic alternates	247
16.2	A typical font encoding file	250
16.3	Glyph sample	253
16.4	Partial font definition file	257
16.5	<code>Nexus</code> font definition file	258
16.6	Sample <code>\fonttable</code> output	260
17.1	\LaTeX input for bibliography example	270
17.2	\BibTeX input for bibliography example	270
17.3	Setting the typesetting engine	271
17.4	Configuring <code>TeXworks</code> for multiple bibliographies	273
17.5	\LaTeX input for indexes example	274
17.6	Sample <code>JabRef</code> bibliography input	276
17.7	<code>JabRef IDE</code>	277
17.8	Creating a new \BibTeX entry	277
17.9	\TeX directory structure	279
18.1	The \TeX Live installation menu on <code>Unix</code>	288
18.2	\LaTeX input for bibliography example	290
18.3	\BibTeX input for bibliography example	290
18.4	Setting the typesetting engine	291
18.5	Configuring <code>TeXworks</code> for multiple bibliographies	292
18.6	\LaTeX input for indexes example	294
18.7	Sample <code>JabRef</code> bibliography input	296
18.8	<code>JabRef IDE</code>	297

18.9	Creating a new <code>BIBTEX</code> entry	297
18.10	<code>TEX</code> directory structure	299
18.11	Baseline and mean line	308
18.12	Bounding boxes	308
18.13	Word formation	308
18.14	Computing the point size	308
18.15	Kerning	309
18.16	Ligatures	309
18.17	Seriffed versus sans serif letters	310

List of Tables

1.1	Depth values of sectional unit commands	31
1.2	Using the <code>\index</code> command	33
2.1	Ten special characters	42
2.2	Common diacritics	44
2.3	Other special characters	44
2.4	Foreign ligatures	45
2.5	Size-affecting declarations and environments	51
2.6	Type style affecting declarations and commands	53
2.7	Latin abbreviations	56
5.1	The <code>xcolor</code> colours	90
5.2	Line width and dash pattern styles	92
5.3	Arrow head types	94
5.4	Node shapes provided by logic gate shape libraries	104
5.5	Shorthand notation for the <code>\foreach</code> command	114
6.1	A poorly designed table	119
6.2	An improved version of Table 6.1	120
7.1	Allowed values for <code>mark</code> option	141
8.1	Lowercase Greek letters	148
8.2	Uppercase Greek letters	149
8.3	Variable-size delimiters	158
8.4	Variable-sized symbols	160
8.5	Log-like functions	162
8.6	Integration signs	163
8.7	Binary operation symbols	165
8.8	Relation symbols	166
8.9	Additional relational symbols	166
8.10	Fixed-size arrow symbols	167
8.11	Extensible arrow symbols provided by <code>amsmath</code>	167
8.12	Extensible <code>mathtools</code> -provided arrow symbols	167
8.13	Options for <code>mathtools</code> -provided arrow symbols	168
8.14	Miscellaneous math mode symbols	168
9.1	Math mode accents, hats, and other decorations	174
9.2	The <code>\overbrace</code> and <code>\underbrace</code> commands	174

9.3	Math mode dot-like symbols	180
9.4	Positive and negative spacing	184
11.1	\TeX 's Expansion Processor	205
12.1	Length units	213
16.1	OpenType font features	246
16.2	Figure feature combinations	247
16.3	<i>Nexus</i> font features	255
17.1	\TeX Live font directories	283
18.1	\TeX Live font directories	303

Preface

THIS BOOK PROVIDES students with an introduction to technical writing and computer presentations with L^AT_EX, which is the de-facto standard in computer science and mathematics. Seasoned L^AT_EX users may also use this work as a reference.

The reader will learn techniques for writing large and complex documents, preparing computer presentations, and creating complex graphics in an integrated manner. The book's website, which may be found at <http://csweb.ucc.ie/~dongen/LAF/LAF.html>, has three separate chapters explaining how to use a widely used L^AT_EX distribution on Windows, on Unix, and on the Mac. These chapters also provide an introduction to some selected integrated development environments (IDES).

For teaching purposes I have tried to minimise the number of classes and style files for the reader. This is one of the main reasons why I decided to use the `amsmath` package for the presentation of mathematics, and decided to use `tikz`, `pgfplots`, and `beamer` for the creation of diagrams, data plots, and computer presentations. Another advantage of this approach is that it simplifies the process of creating a viewable/printable output file. Everything should work with `pdflatex`, which is a program that turns L^AT_EX into pdf.

Beginners can be challenged by what are known in the L^AT_EX community as “verbatim” commands and environments, except when it comes to including, well, verbatim program listings. To avoid errors that are difficult to find and are not always so easy to resolve, these verbatim commands do not appear in this volume. By no means should the decision to omit verbatim commands be a limitation; this work was written without verbatim commands. You likely could write a thesis or dissertation without them too.

M. R. C. van Dongen
Cork
2011

Book Outline

THIS BOOK has seven parts, some of which are more technical than others. The following is a short outline.

The first two parts are called *Basics* and *Basic Typesetting*. These parts introduce the reader to the basic L^AT_EX commands for typesetting and cross-referencing. They also explain how to create one or several bibliographies and one or several indexes or glossaries.

The next part is *Tables, Diagrams, and Data Plots*, which is about presenting data in tables, diagrams with the `tikz` package, and data plots with the `pgfplots` package.

Mathematics and Algorithms is the next part. It explains how to typeset mathematics, how to typeset algorithms in pseudo-code, and how to present program listings.

This is followed by *Automation*, which explains how to implement user-defined commands, how to implement option parsing, and how to implement conditional branching. Some readers may wish to skip this part because it is more technical than the other parts.

Miscellany is the next part. It is a collection of optional chapters, some of which are of a more technical nature than others. The first, relatively easy, chapter explains how to create computer presentations with the `beamer` package. It continues with two more technical chapters that explain how to implement user-defined classes and packages and how to use OpenType fonts.

The last part is *References and Bibliography*, which is a collection of indexes, a list of acronyms, a bibliography, and a short typographic jargon reference. Readers not familiar with notions such as characters, glyphs, ligatures, serifs, kerning, fonts, typefaces, points, point size and leading, ems, and ens, are invited to start with the jargon reference before reading the rest of the book.

Overall, the chapters are well balanced but the chapters about typesetting mathematics and presenting diagrams with `tikz` are a bit longer and more detailed. This is why it was decided to split the presentation on typesetting mathematics into two separate chapters. The first of these chapters should be sufficient for most readers. The chapter about presenting diagrams with `tikz` was not split because it was felt that most readers who are interested in some of this chapter would also be interested in the rest.

Acknowledgements

THIS BOOK would not have been possible without the help of many. First of all, I should like to thank Don Knuth for writing $\text{T}_{\text{E}}\text{X}$ and Leslie Lamport for writing $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$ —without them the landscape of computer-based typesetting would have been dominated by Bill. I should like to thank Eddie Kohler for writing `otftotfm` and for his help. I am grateful to Till Tantau and colleagues for writing the beautiful `tikz` package and the `beamer` class. Both of them are stars in terms of functionality, productivity, and documentation. Thanks to David Farley and Dario Taraborelli for letting me include the pictures in Figures 4.2 and 16.1. Many thanks to Billy Foley and the University College Cork Art Collection for letting me include the pictures at the back of the part titlepages. I should like to thank Charles P. Schaum, Frank Böhme, George Boyle, Tom Carroll, Finbarr Holland, Rik Kabel, Mico Loretan, Ben McKay, Luca Merciadri, Oliver Nash, Oleg Paraschenko, Jason Quinlan, Lisa Swenson, Uwe Ziegenhagen, and Wim Michels for useful comments on early drafts. I should also like to thank Paul Blaga, Robin Fairbairns, Peter Flynn, Francisco A. F. Reinaldo, and Boris Veytsman for reviewing the book. Special thanks to Joseph Wright who was so kind to proofread the entire book and to write the foreword. His critical eye spotted many known and unknown errors. Many thanks to Mr Engesser, Ms Glaunsinger, and Ms Fisher at Springer for providing the opportunity to publish this book and for helping me bring this project to a successful end. Finally, I should like to thank all those who have worked on $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$ and friends, all those who have supported $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$ and friends, and all who have answered all my $\text{L}^{\text{A}}\text{T}_{\text{E}}\text{X}$ and `METAPOST` questions over the last two decades or so. The following are but a few: André Heck, Barbara Beeton, Cristian Feuersänger, Dan Luecking, David Carlisle, David Kastrup, Denis Roegel, Donald Arseneau, D. P. Story, Frank Mittelbach, Frank van Raalte, Hans Hagen, Heiko Oberdiek, Jim Hefferon, John Hobby, Jonathan Fine, Jonathan Kew, Karl Berry, Kees van der Laan, Keith Reckdahl, Kjell Magne Fauske, Mark Wibrow, Nelson Beebe, Peter Wilson, Philipp Lehman, Rainer Schöpf, Ross Moore, Scot Pakin, Sebastian Rahtz, Stephan Hugel, Taco Hoekwater, Thomas Esser, Ulrike Fisher, Victor Eijkhout, Vincent Zoonekynd, Will Robertson, and all the many, many others. Without them the $\text{T}_{\text{E}}\text{X}$ community would have been much worse off.

PART I

Basics

Picture omitted to keep size of .pdf small.

Untitled Landscape, oil on paper (1993), 64 × 90 cm
Work included courtesy of Billy Foley and University College Cork Art Collection
© Billy Foley (www.billyfoley.com) and University College Cork Art Collection

PART II

**Basic
Typesetting**

Picture omitted to keep size of .pdf small.

Oil and charcoal on canvas (31/08/05), 183 × 223 cm
Work included courtesy of Billy Foley
© Billy Foley (www.billyfoley.com)

CHAPTER 2

Running Text

THIS CHAPTER EXPLAINS everything you've always wanted to know about writing text, aligning it, and changing text appearance.

Recall from Chapter 1 that L^AT_EX is implemented on top of T_EX, which is a rewriting machine that turns token streams into token streams. Some of the character tokens in the input stream have a special meaning to T_EX. This is studied in Section 2.1. The rest of the chapter is about typesetting. We start with some sections about diacritics, ligatures, dashes, emphasis, footnotes and marginal notes, quotes and quotations. If you're not familiar with these notions then don't worry, because they are explained further on. Also you can visit the typography jargon reference on page 307. This chapter ends with sections about changing the size and the type style of the text, the most important text alignment techniques, and language related issues.

2.1 Special Characters

This section studies ten characters that have a special meaning to T_EX. When T_EX sees these characters as tokens in the input stream, then it usually does not typeset them but, instead, changes state. The remainder of this section briefly explains the purpose of the tokens and how you typeset them as characters in the output.

Table 2.1 depicts the tokens, their meaning, and the command to typeset them. We have already studied the start-of-comment token (%) and the backslash (\), which starts control sequences. Typesetting a backslash is done with the commands `\textbackslash` and `\backslash`. The latter command is only used when specifying mathematical formulae, which is described in Chapter 8. The parameter reference token is described in Chapter 11. The alignment tab (&) is described in Section 2.19.3. This token usually indicates a horizontal alignment position in array-like structures consisting of rows and columns. The math mode switch token (\$), the subscript token (_), and the explained token (^) are described in Chapter 8. The three remaining tokens are described in the remainder of this section.

2.1.1 *Tieing Text*

Remember that L^AT_EX is a large rewriting machine that repeatedly turns token sequences into token sequences. At some stage it turns a

Table 2.1

The characters in the first column have a special meaning to \LaTeX . The purpose of the characters is listed in the column 'Purpose.' The last column lists the command that produces the character. The command `\textbackslash` is used when typesetting normal text. The command `\backslash` is used when typesetting mathematics.

Token	Purpose	Command for Plain Character
#	parameter reference	<code>\#</code>
\$	math mode switch	<code>\\$</code>
%	start of comment	<code>\%</code>
&	alignment tab	<code>\&</code>
~	text tie token	<code>\textasciitilde</code>
_	math subscript	<code>_</code>
^	math superscript	<code>\textasciicircum</code>
{	start of group	<code>\{</code>
}	end of group	<code>\}</code>
\	start of command	<code>\textbackslash</code> or <code>\backslash</code>

token sequence into lines. This is where \LaTeX (\TeX really) determines the line breaks. The tilde token (`~`) defines an inter-word space that cannot be turned into a line break. As such it may be viewed as an operator that ties words.

The following shows two important applications of the tilde operator: it prevents unpleasant linebreaks in references and citations.

```
... Figure~\ref{fig:list@format}
depicts the format of a list.
It is a reproduction of~\cite[Figure~6.3]{Lamport:94}.
```

\LaTeX Usage

It is usually not too difficult to decide where to use the tie operator. The following are some concrete examples, which are taken from [Knuth 1990, Chapter 14].

- References to named parts of a document:
 - * Chapter~12,
 - * Theorem~1.5,
 - *

Knuth [1990] recommends that you use `Lemmas 5` and `~6` because having the 5 at the start of a line is not really a problem.
- Between a person's forenames and between multiple surnames:
 - * Donald~E. Knuth,
 - * Luis~I. Trabb~Pardo,
 - * Bartel~Leendert van~der~Waarden,
 - * Charles~XII,
 - *
- Between math symbols in apposition with nouns:
 - * dimension~ $\$d\$,$
 - * string~ $\$s\,$ of length~ $\$l\$,$
 - *

Here the construct `\langle math \rangle` is used to typeset `\langle math \rangle` as an in-line mathematical expression.
- Between symbols in series:
 - * 1,~2, or~3.
- When a symbol is a tightly bound object of a preposition:

- * from 0 to~1,
- * increase $\$z\$$ by~1,
- * ...
- o When mathematical phrases are rendered in words:
 - * equals~ $\$n\$$,
 - * less than~ $\$\epsilon\$,$
 - * modulo~ $\$2\$$,
 - * for large~ $\$n\$$,
 - * ...
- o When cases are being enumerated within a paragraph:
 - * Show that function $f(x)$ is (1)~continuous; (2)~bounded.

2.1.2 Grouping

Grouping is a common technique in L^AT_EX. The opening brace ({) starts a group and closing brace (}) closes it. Grouping has two purposes. The first purpose of grouping is that it turns several things into one compound thing. This may be needed, for example, if you want to pass several words to a command that typesets its argument in bold face text. The following demonstrates the point.

```
A bold \textbf{word} and      A bold word and a bold letter.
a bold \textbf letter.
```

The second purpose of grouping is that it lets you change certain settings and keep the changes local to the group. The following demonstrates how this may be used to make a local change to the type style of the text inside the group.

```
Normal text here.
{% Start a group.
  \bfseries          Normal text here. Bold paragraphs in here. Back to normal
  % Now we have bold text.      text again.
  Bold paragraphs in here.
}% Close the group.
Back to normal text again.
```

Inside the group you may have several paragraphs. The advantage of the declaration `\bfseries` is that it defines how the text is typeset until the end of the group. The `\textbf` command just typesets its argument in a bold typeface. The argument may not contain paragraph-breaks.

There is also a low-level T_EX mechanism for creating groups. It works just as the braces. A group is started with `\begingroup` and ended with `\endgroup`. These tokens may be freely mixed with braces but `{ }` pairs and `\begingroup/\endgroup` pairs should be properly matched. So `{ \begingroup \endgroup }` is allowed but `{ \begingroup } \endgroup` is not. A brace pair affects whitespace when you're typesetting mathematics but a `\begingroup/\endgroup` pair does not.

Table 2.2
Common diacritics

Output	Command	Name
ò	\' {o}	Acute accent
ó	\' {o}	Grave accent
ô	\^ {o}	Circumflex (hat)
õ	\~ {o}	Tilde (squiggle)
ö	\" {o}	Umlaut or dieresis
ċ	\. {c}	Dot accent
š	\v {s}	Háček (caron or check)
ö	\u {o}	Breve accent
ō	\= {o}	Macron (bar)
ő	\H {o}	Long Hungarian umlaut
ȫ	\t {oo}	Tie-after accent
ş	\c {s}	Cedilla accent
ȯ	\d {o}	Dot-under accent
o̅	\b {o}	Bar-under accent

Table 2.3
Other special characters

Output	Command	Name
å	\aa	Scandinavian a-with-circle
Å	\AA	Scandinavian A-with-circle
ł	\l	Polish suppressed-l
Ł	\L	Polish suppressed-L
ø	\o	Scandinavian o-with-slash
Ø	\O	Scandinavian O-with-slash
¿	?'	Open question mark
¡	!'	Open exclamation mark

2.2 Diacritics

This section studies how to typeset characters with *diacritics*, which are also known as accents. Table 2.2 displays some commonly occurring diacritics and the commands that typeset them. The presentation is based on [Knuth 1990, Chapter 9].

Using `\" {i}` to typeset *ï* may not work if you're not using a Type 1 font (T1 font). However, typesetting *ï* with `\" {\i}` should always work. Here the command `\i` is used to typeset a dotless *i* (*ı*). There is also a command `\j` for a dotless *j*.

Table 2.3 shows some other commonly occurring special characters.

2.3 Ligatures

A ligature combines two or several characters as a special glyph. Examples of English ligatures and their equivalent character combinations are *fi* (`fi`), *ff* (`ff`), *ffi* (`ffi`), *fl* (`fl`), and *and* (`and`). L^AT_EX recognises English ligatures and substitutes them for the characters representing them.

Table 2.4 displays some foreign ligatures. The symbol *ß* (eszett) is

Output	Command	Name
œ	\oe	French ligature œ
Œ	\OE	French ligature Œ
æ	\ae	Scandinavian ligature æ
Æ	\AE	Scandinavian ligature Æ
ß	\ss	German ‘Eszett’ or sharp S

Table 2.4
Foreign ligatures

‘Convention’ dictates that punctuation go inside quotes, like ‘‘this,’’ but some think it’s better to do ‘‘this’’.	‘Convention’ dictates that punctuation go inside quotes, like “this,” but some think it’s better to do “this”.
--	--

Figure 2.1
Quotes

<code>‘\,’Fi’ or ‘fum?’\,’</code> he asked. \\	“‘Fi’ or ‘fum?’” he asked.
<code>‘‘‘Fi’ or ‘fum?’’’</code> he asked. \\	“‘‘Fi’ or ‘fum?’’’ he asked.
<code>‘{’Fi’ or ‘fum?’{’}</code> he asked.	“‘Fi’ or ‘fum?’” he asked.

Figure 2.2
Nested quotations

a ligature of fs [Bringhurst 2008] and this is reflected in the \LaTeX command that typesets the symbol.

Sometimes it is better to suppress ligatures. The following is an example: the `\makebox` command prevents \LaTeX from turning the fi in selfish into a ligature, which makes the result much easier to parse: selfish, not selfish.

```
Mr~Crabs is a self\makebox{}ish shellfish.  $\LaTeX$  Usage
```

Other words that need “anti-hyphenation” pre-processing are halflife, halflife, selfless, offline, offloaded, and so on.

2.4 Quotation Marks

This section explains how you typeset quotation marks. Figure 2.1 is an example from [Lamport 1994, page 13]. The word ‘Convention’ in this example is in single quotes and the word ‘this’ is in double quotes. The quotes at the start are backquotes (‘ and ‘). The quotes at the end are the usual quotes (’ and ’). Notice that output quote between ‘it’ and ‘s’ is produced using a single quote in \LaTeX .

To get properly nested quotations you insert a thin space where the quotes “meet.” Recall that the thin space command (`\,`) typesets a thin space. Figure 2.2 provides a concrete example that is taken from [Lamport 1994, page 14]. Figure 2.2 provides another example. The first line of this example looks much better than the other two. Note that \LaTeX parses three consecutive quotes as a pair of quotes followed by one more quote. This is demonstrated by the second line of the output, which looks terrible. The last line of the input avoids the three consecutive quotes by adding an empty group that makes

explicit where the double quotes and the single quote meet. Still the resulting output doesn't look great.

Intermezzo. As a general rule, British usage prefers the use of single quotes for ordinary use. This poses a problem if an apostrophe is used for the possessive form: He said 'It is John's book.' This is why it is also acceptable to use double quotes [Trask 1997, Chapter 8].

2.5 Dashes

There are three kinds of dashes: -, –, and —. In L^AT_EX you get them by typing -, --, and ---. The second symbol can also be typeset with the command `\textendash` and the last symbol with the command `\textemdash`. The symbol –, which is used in mathematical expressions such as $a - b$, is not a dash. This symbol is discussed in Chapter 8. The following briefly explains how the dashes are used.

- This is the intra-word dash, which is used to hyphenate compound modifiers such as one-to-one, light-green, and so on [Trask 1997, Chapter 6]. In L^AT_EX you typeset this symbol as follows: -.
- This is the en-dash, which has the width of 1 en. An en is equivalent to half the *current* type size, so an en-dash is shorter in normal text than it is in large text. The en-dash is mainly used in ranges: pages 12–15 (from 12 to 15). However, the en-dash is also used to link two names that are sharing something in common: a joint Anglo–French venture [Allen 2001, page 45]. The L^AT_EX command `\textendash` and the sequence -- typeset the en-dash. When you typeset an en-dash, it looks better if you add a little space before and after. Remember that \, produces a thin space. Use this command for the horizontal space.

```
... pages~12\,--\,15 (from~12 to~15).
```

L^AT_EX Usage

- This is the em-dash, which has the same width as an em. An em is equal to the *current* type size. The em-dash separates strong interruptions from the rest of the sentence—like this [Trask 1997, Chapter 6]. Bringhurst [2008, page 80] prefers the en-dash to the em-dash. The L^AT_EX command `\textemdash` and the sequence --- typeset the em-dash. An em-dash at the start of a line doesn't look very good so you should tie each em-dash to the preceding word.

```
... the rest of the sentence~\textemdash  
like this~\parencite[Chapter~6]{Trask:1997}.
```

L^AT_EX Usage

Figure 2.3 presents an example of the dashes. A few years ago I noticed that sometimes --- doesn't work with X_YL^AT_EX (even with Mapping = tex-text enabled). However, `\textemdash` always worked.

2.6 Full Stops

L^AT_EX usually treats a full stop (.) as an end-of-sentence indicator. By

The intra-word dash is used to hyphenate compound modifiers such as light-green, X-ray, or one-to-one. ...

The en-dash is used in ranges: pages~12--15.

The em-dash is used to separate strong interruptions from the rest of the sentence~--- like this%
`~\cite[Chapter~6]{Trask:1997}. ...`

Figure 2.3

Dashes

default, \LaTeX inserts a bit more space after the full stop at the end of a sentence than it does between words. It also does this after other punctuation symbols. The `\frenchspacing` command turns this feature off. The command `\nonfrenchspacing` turns the feature on again. When a full stop is not the end of a sentence you need to help \LaTeX a bit by inserting the space command (`\.`) after the full stop.

```
Meet me at 6~p.m.\.at the Grand Parade.  $\LaTeX$  Usage
```

However, when an uppercase letter is followed by a full stop, then \LaTeX assumes the full stop is for abbreviation. For example:

```
Donald~E. Knuth developed the {\TeX} system.  $\LaTeX$  Usage
```

This convention causes a problem if an uppercase letter really is the end of a sentence. Insert a `\@` before the full stop if this happens.

```
In Frank Herbert's \emph{Dune} saga,  $\LaTeX$  Usage
the Mother School of the Bene Gesserit
is situated on the planet Wallach IX\@.
```

\LaTeX inherits its habit of putting some extra space after full stops and other punctuation symbols from \TeX . Bringhurst [2008, pages 28–30] points out that there really is no reason to add such extra space for modern works. Following Bringhurst's advice, this document was typeset with `\frenchspacing` enabled.

2.7 Ellipsis

The command `\ldots` produces an ellipsis (...), which is used to indicate an omission. If the ellipsis occurs at the end of a sentence, then you still need to add an end-of-sentence marking full stop. If this happens then Felici [2012, Figure 13.15] recommends that you put the ellipsis close to the preceding text and then add the full stop.

<pre>Many stories start with 'Once upon a time\ldots.' They usually end with '\ldots\and they all lived happily ever after.'</pre>	<pre>Many stories start with 'Once upon a time....' They usually end with '... and they all lived happily ever after.'</pre>
--	--

Figure 2.4 Robert Bringhurst, author of
Good borderline punctuation
`\emph{Elements of
 Typographic Style,}`
 recommends setting such
 punctuation symbols in
 the brighter type.
`\textbf{Do as he},` or
 risk getting ugly type.

Robert Bringhurst, author of *Elements of Typographic Style*, recommends setting such punctuation symbols in the brighter type. **Do as he**, or risk getting ugly type.

Figure 2.5 Robert Bringhurst, author of
Poor borderline punctuation
`\emph{Elements of
 Typographic Style},`
 recommends setting such
 punctuation symbols in
 the brighter type.
`\textbf{Do as he,}` or
 risk getting ugly type.

Robert Bringhurst, author of *Elements of Typographic Style*, recommends setting such punctuation symbols in the brighter type. **Do as he**, or risk getting ugly type.

2.8 Emphasis

Emphasis is a typographic tool for typesetting text in a different typeface. The idea is that this makes the text stand out. Emphasis is especially useful when introducing a new concept, such as in this paragraph.

In some documents, emphasis is implemented by typesetting text in a bold face typeface, by typesetting it in uppercase typeface, or (worse) by underlining the text. L^AT_EX emphasises text in paragraphs by italicising the text. Trask [1997, page 82] calls this the preferred style for emphasis. The L^AT_EX command for emphasis is `\emph`.

Emphasised `\emph{example.}` Emphasised *example.*

2.9 Borderline Punctuation

Bold text looks darker than normal, upright text and italicised text look brighter than normal, upright text. When small punctuation symbols get caught between darker and brighter type it is time to pay attention. Robert Bringhurst, author of *Elements of Typographic Style*, recommends setting such punctuation symbols in the brighter type [Bringhurst 2008]. **Do as he**, or risk getting ugly type. Figures 2.4 and 2.5 demonstrate what you get if you follow Bringhurst's advice and what if you don't. The figures do not excel in terms of maintainability because they hardcode the author's name and the title of the work.

2.10 Footnotes and Marginal Notes

It is generally accepted that using footnotes and marginal notes should be used sparingly because they are disruptive. However, proper use of

```
Footnotes\footnote{A footnote is a note
of reference, explanation, or comment that is
usually placed below the text on a printed page.}
can be a nuisance. This is especially true if
there are many.\footnote{Like here.} The more you see
them, the more annoying they get.\footnote{Got it?}
```

Footnotes^a can be a nuisance. This is especially true if there are many.^b The more you see them, the more annoying they get.^c

^aA footnote is a note of reference, explanation, or comment that is usually placed below the text on a printed page.

^bLike here.

^cGot it?

Figure 2.6

Using footnotes

marginal notes in documents with wide margins can be very effective.

Not surprisingly, L^AT_EX provides a command for footnotes and a command for marginal notes. Figure 2.6 demonstrates how to specify footnotes in L^AT_EX. A *marginal note* or *marginal paragraph* is like a footnote, but placed in the margin as on this page. The command `\marginpar{<text>}` puts `<text>` in the margin as a marginal note. By passing an optional argument to the command you can put different text on odd (recto/front/right) pages and on even (verso/back/left) pages. The optional argument is used for even pages and the required argument is used for odd pages. If you're using both the optional and required argument then it is easy to remember which is which: the optional argument is to the left of the required argument so it's for the left page; the required argument is for the right page. Note that narrow marginal notes may look better with ragged text, which is text that is aligned to one side only. On the right (left) pages you use ragged right (left) text. Section 2.19.2 explains how to typeset ragged text.

Avoid marginal notes in very narrow margins.

2.11 Displayed Quotations and Verses

The `quote` and `quotation` environments are for typesetting displayed quotations. The former is for short quotations; the latter is for longer quotations. Figure 2.7 shows how you use the `quote` environment. The command `\\` in Figure 2.7 forces a line break.

The `verse` environment typesets poetry and verse. Figure 2.8 shows how you use the environment. In this example, the command `\qqquad` inserts two quads. Here a quad is an amount of space that is equivalent to the *current* type size. So if you use a 12 pt typeface then a quad results in a 12 pt space in normal text. The command `\\` inside the `verse` environment determines the line breaks. Remember that the command `\,` before the letter *S* inserts a thin space.

2.12 Line Breaks

In the previous section, the command `\\` inserted a line break in displayed quotations and verses. The command also works inside

Figure 2.7 Blah blah blah blah blah blah blah blah blah. The quote environment

```
\begin{quote}
  Next to the originator of a good sentence
  is the first quoter of it. \\
  \emph{Ralph Waldo Emerson}
\end{quote}
Blah blah blah blah blah blah blah blah blah.
```

Blah blah blah blah blah blah blah blah blah.

Next to the originator of a good sentence is the first
quoter of it.
Ralph Waldo Emerson

Blah blah blah blah blah blah blah blah blah.

Figure 2.8 The following anti-limerick is attributed to W. S. Gilbert. The verse environment

```
\begin{verse}
  There was an old man of St.~Bees,          \\
  Who was stung in the arm by a wasp;        \\
  \quad \quad \quad When they asked, "Does it hurt?" \\
  \quad \quad \quad He replied, "No, it does n't,    \\
  But I thought all the while 't was a Hornet.'"
\end{verse}
```

The following anti-limerick is attributed to W. S. Gilbert.

There was an old man of St. Bees,
Who was stung in the arm by a wasp;
 When they asked, "Does it hurt?"
 He replied, "No, it does n't,
But I thought all the while 't was a Hornet."

paragraphs. An optional argument determines the extra vertical space of the line break: `\\[⟨extra vertical space⟩]`. A line break at the end of a page may trigger a page break. If you don't want a page break then you should use the command `*`. It is identical to `\\` but it inhibits page breaks.

2.13 Controlling the Size

With the proper class and packages there is usually no need to change the type size of your text. However, sometimes it has its merits, e.g., when you're designing your own titlepage or environment. Table 2.5 lists the declarations and environment that change the type size. The preferred "size" for long-ish algorithms and program listings is `\scriptsize`. If you're using a package to typeset listings then the package usually chooses the right size. If not, it probably lets you specify the type size. Figure 2.9 shows how you change the size of text.

Declaration	Environment	Example
<code>\tiny</code>	<code>tiny</code>	Example
<code>\scriptsize</code>	<code>scriptsize</code>	Example
<code>\footnotesize</code>	<code>footnotesize</code>	Example
<code>\small</code>	<code>small</code>	Example
<code>\normalsize</code>	<code>normalsize</code>	Example
<code>\large</code>	<code>large</code>	Example
<code>\Large</code>	<code>Large</code>	Example
<code>\LARGE</code>	<code>LARGE</code>	Example
<code>\huge</code>	<code>huge</code>	Example
<code>\Huge</code>	<code>Huge</code>	Example

Table 2.5
Size-affecting declarations and environments

```

{\tiny Mumble.      \\
 \begin{normalsize}
   What?
 \end{normalsize}  \\
 \begin{Huge}
   Mumble!
 \end{Huge} }

```

Mumble.
What?

Mumble!

Figure 2.9
Controlling the size

2.14 Seriffed and Sans Serif Typefaces

L^AT_EX has several commands that change the type style. Before studying these commands it is useful to study the difference between seriffed and sans serif typefaces and when to use them.

A *serif* is a little decoration at the end of some of the strokes of some of the letters. In a *seriffed* typeface the letters have serifs. Seriffed typefaces are sometimes called *roman* typefaces but in L^AT_EX roman means upright. In a *sans serif* typeface the letters lack serifs.

Most books use a seriffed typeface for the running text [Unger 2007, pp. 167–168] and the most popular typeface for the running text of books and reports is (*Monotype/Linotype*) *Times Roman* [Felici 2012], a seriffed typeface. Seriffed typefaces are also used for the running text of most papers, theses, and dissertations in science. Turabian [2007, pp. 374–375] recommends that you use a typeface that is designed for text and that you use a size in the range of 10–12 pt, with 12 pt being the preferred size. Admittedly, the being designed for text is a bit vague but Turabian [2007] give two examples, both of which are seriffed.

As lines get longer and longer, seriffed typefaces are easier to read and make fast reading easier [Unger 2007]. Sans serif typefaces may look better on the screen but the ultimate criterion for printed matter is how the text looks in print, so never choose the typeface for your printed text based on how it looks on the screen.

If a typeface family has a seriffed and sans serif typeface of the same

type size (point size), then the seriffed typeface usually requires more horizontal space [Unger 2007]. Stated differently, sans serif typefaces are usually more efficient when it comes to saving space. This may be exploited by using sans serif typefaces in captions, in brochures, in short narrow columns, or on road signs [Unger 2007].

If you don't change the typeface then \LaTeX will typeset the body of your document in *Computer Modern*. An example of *Computer Modern* may be found in Table 2.6, further on in this chapter.

2.15 Small Caps Letters

Small caps letters are used to typeset acronyms and abbreviations. Their shape is the same as uppercase letter but their height is smaller, which lets them blend in better with the rest of the text. For example, compare NO SHOUTING with NO SHOUTING. The latter is easier on the eye.

Adding extra space uniformly to the left and right of characters in a passage of text is called tracking or letterspacing. The extra space that is added per letter is called the tracking space. Tracking passages of small caps text is a common technique to improve the legibility. For example NON-SPACED SMALL CAPS is not spaced, whereas SPACED SMALL CAPS is letterspaced.

The command `\textsc` typesets lowercase letters in small caps. The easiest way to automatically letterspace such text is to use the `microtype` package with the option `tracking=smallcaps`. After this all small caps text will be letterspaced.

```
\textsc{No shouting}.           NO SHOUTING.
```

The `microtype` package also provides character protrusion (margin kerning) and font expansion. Character protrusion adjusts the characters at the margins of the text. Font expansion uses narrow or wider font versions so as to make the overall appearance of the text more uniform, avoiding long cramped, dark lines with many characters and long loose, bright lines with few characters. As a side-effect, font expansion may also be used to choose better hyphenation points [Schlicht 2010]. This document was typeset using the `microtype` package with the following options.

```
\usepackage[final,tracking=smallcaps,            $\text{\LaTeX}$  Usage
                expansion=alltext,protrusion=true]{microtype}
```

Bringhurst [2008, page 30] recommends that you add 5–10% of the type size (point size) for the tracking space. The `microtype` package expects the extra tracking in thousands of the type size. The following sets the tracking space to 5% for the `sc` (small caps) shape.

```
\SetTracking{encoding=*,shape=sc}{50}            $\text{\LaTeX}$  Usage
```

Most `microtype` users agree that the package improves the appearance of their documents.

Declaration	Command	Example
<code>\mdseries</code>	<code>\textmd</code>	Medium Series
<code>\normalfont</code>	<code>\textnormal</code>	Normal Style
<code>\rmfamily</code>	<code>\textrm</code>	Roman family
<code>\upshape</code>	<code>\textup</code>	Upright Shape
<code>\itshape</code>	<code>\textit</code>	<i>Italic Shape</i>
<code>\slshape</code>	<code>\textsl</code>	<i>Slanted Shape</i>
<code>\bfseries</code>	<code>\textbf</code>	Boldface Series
<code>\scshape</code>	<code>\textsc</code>	SMALL CAPS SHAPE
<code>\sffamily</code>	<code>\textsf</code>	Sans Serif Family
<code>\ttfamily</code>	<code>\texttt</code>	Typewriter Family

Table 2.6

Type style affecting declarations and commands. The last column shows the result in *Computer Modern* (L^AT_EX’s default typeface). The first four lines usually correspond to the default style. The first nine typefaces are proportional. They may have glyphs with different widths, e.g., compare *M* and *i*. Small caps letters are useful for abbreviations. The last typeface is non-proportional, which is useful in program listings.

2.16 Controlling the Type Style

Changing the type size is hardly ever needed in an article, thesis, report, or book. Changing the type style is required much more, but usually this is done automatically by the commands that typeset the title of your document, the section titles, the captions, and so on.

There are ten L^AT_EX type style affecting declarations. Each declaration has a command that takes an argument and applies the type style of the declaration to the argument. The arguments cannot have paragraph breaks. The declarations and commands are listed in Table 2.6.

Intermezzo. If you really must change the type style of your text then it is probably for a specific purpose. For example, to change the type style of a newly defined word, to change the type style of an identifier in an algorithm, and so on. Rather than hard-coding the style in your input, it is better if you define a user-defined command that typesets your text in the required style and use the command to typeset your text. The command’s name should reflect its purpose. For example `\identifier` to typeset an identifier in an algorithm, `\package` to typeset the name of a L^AT_EX package, and so on. Using this approach improves maintainability. For example, if you want to change the type style of all identifiers in your text then you only need to make changes in the definition of the command that typesets identifiers. Defining your own commands is discussed in Chapter 11.

2.17 Abbreviations

This section is about abbreviations. It provides some guidelines about their spelling and how to typeset them in L^AT_EX.

2.17.1 Initialisms

Abbreviations that are made up of the initial letters of the abbreviated words are called *initialisms*. Non-standard initialism are usually written with a full stop after each part in the abbreviation: Ph.D. (Philosophiae

Figure 2.10 Finer points of typesetting abbreviations

In 2010 Prof. Donald Knuth was invited to the annual TeX User Group Conference in San Francisco, Ca. to speak about a revolutionary successor to TeX. This remarkable system is entirely menu driven and incorporates facilities for social networking. Pronouncing the name involves making the sound of a bell.

Doctor), D.Phil. (Doctor of Philosophy), M.Sc. (Master of Science), and so on. However, if the initialisms are standard, then you omit the full stops, so B.B.C. becomes BBC, 4 G.L. (fourth-Generation Language) becomes 4GL, and Ph.D. becomes Ph D (in L^AT_EX Ph~D). Bringhurst [2008, page 48] recommends typesetting abbreviations with more than two uppercase letters in spaced small capitals: SPACED SMALL CAPS. Section 2.15 explains how to get spaced small caps.

Some authors recommend that you letterspace Uniform Resource Locators (URLs), phone numbers, and email addresses because they are not words. See for example [Bringhurst 2008] or [Hedrick 2003].

Abbreviations of personal names such as D. E. K., J. F. K., J. S. B., and the like should not be letterspaced.

2.17.2 Acronyms

An *acronym* is an initialism that is pronounced as a word. For example, radar (Radio Detection And Ranging), sonar (SOund Navigation And Ranging), NASA (National Aeronautics and Space Administration), and EBCDIC (Extended Binary Coded Decimal Interchange Code); but not ACM (Association for Computing Machinery), BBC (British Broadcasting Corporation), and RSVP (Répondez S'il Vous Plaît). Note that not all acronyms are spelt with uppercase letters; if you're not certain, look up the spelling. Since acronyms are just a special form of initialisms, we should follow Bringhurst's advice, and write them with small caps if they are spelt with (two or more) uppercase letters.

2.17.3 Shortenings

A word that is abbreviated by taking the first few letters of that word is called a *shortening*. To avoid ambiguity, shortenings are usually written with a full stop at the end of each part. For example, p. (page), proc. (proceedings), sym. (symposium), fig. (figure), Feb. (February), Prof. (Professor), and so on. The abbreviation pp. is for pages.

Remember that L^AT_EX inserts a little extra white space after a full stop if `\frenchspacing` isn't enabled. If an abbreviation is not at the end of a sentence and ends with a full stop then this extra space may look bad. To suppress the extra white space you have to hardcode a space command (`_`) after the abbreviation or tie the abbreviation and the following word. Figure 2.10 provides a small example.

2.17.4 *Introducing Abbreviations*

The first time you introduce an abbreviation you should explain it. Most authors first spell out the abbreviation and then provide the abbreviation in parenthesis. The `acronym` package provides some support for defining and referencing abbreviations in a consistent style. This is done using the standard label-referencing technique. The package provides commands for singular and plural versions of abbreviations and for abbreviated and unabbreviated versions.

Page 4 of this book introduces an acronym for integrated development environments. This text was generated by the following input.

```
... many \acp{IDE} ... LATEX Input
```

The command `\acp` in this example is provided by the `acronym` package. The command introduces the plural version of an abbreviation. The `acronym` package also provides the `\ac` command, which introduces the singular version of an abbreviation. The argument `IDE` of the `\acp` command is the label of the acronym. Some other part of the input associates the label `IDE` with the abbreviated version ‘`IDE`’ and the expanded version ‘Integrated Development Environment.’ This was (essentially) done as follows:

```
\acro{IDE} [\textsc{ide}]% LATEX Input
  {Integrated Development Environment}
```

When this book was generated and the command `\acp` was used in the second last input, this was the first time the label `IDE` was referenced, which is why it resulted in the following output.

```
... many Integrated Development Environments (IDES) ... LATEX Output
```

The label `IDE` is also referenced in other locations in the input, but when that happens it always results in the abbreviated version of the acronym: `IDE`. More information about the `acronym` package may be found in the package documentation [Oetiker 2010].

2.17.5 *British and American Spelling*

There are differences between American and British usage in time abbreviations. According to Trask [1997] Americans write 10:05 AM (Ante Meridiem) for five past ten in the morning and 13:15 PM (Post Meridiem) for a quarter past one in the afternoon. British spelling prefers 10.05 a.m. and 13.15 p.m. [Trask 1997]. Felici [2012] notices that Americans have also started using the British form.

For titles such as Mister, Doctor, and so on, British and American usage differ. British usage is the same as for shortenings. For example, Mr Happy, Dr Who, and Fr Dougal McGuire. Americans add the full stop: Mr. Ed, Dr. Quinn, Medicine Woman, and Fr. Bob Maguire.

Table 2.7

Latin abbreviations. The first column lists the abbreviations, the second the original Latin meaning, and the last the English translation. Note that the abbreviations at the bottom of the table are slanted. This is intentional and preferred usage.

Abbreviation	Latin meaning	English meaning
e.g.	exempli gratia	for example
i.e.	id est	that is/in other words
etc.	et cetera	and so forth
<i>viz.</i>	videlicet	that is to say/namely
<i>cf.</i>	confer	compare
<i>et al.</i>	et alii/aliae/alia	and others

2.17.6 Latin Abbreviations

This section studies some Latin abbreviations that are commonly used in scientific writing. Table 2.7 presents the more commonly occurring abbreviations, their Latin meaning, and the English translation.

Note that some abbreviations are typeset in italics. This is not by accident: this is how they should be typeset—but conventions may differ from field to field. Also note that the *al* in *et al.* gets a full stop because it is an abbreviation of *aluis* but that the *et* does not get a full stop because it is already spelt out in full. Remember Bringhurst’s advice and put the full stop inside the argument of `\emph: \emph{et al.}` Finally note that *etc.* is short for *et cetera*, not for *ectcetra*.

Trask [1997] discourages these abbreviations. Trask continues by pointing out that writing statements like the following are wrong because the reader should be invited to consult the reference.

The Australian language Dyrbal has a remarkable gender system, *cf.* [Dixon 1972].

Trask proposes the following solution.

The Australian language Dyrbal has a remarkable gender system; see [Dixon 1972].

Abbreviations such as *etc.*, *i.e.*, and *e.g.* require additional punctuation [Strunk, and White 2000]:

- Abbreviations such as BBC, NBC, etc., are called initialisms.
- Shortenings, *i.e.*, abbreviations that are formed by taking the first letters of the abbreviated word, usually end with a full stop.
- Abbreviations are not always spelt the same, *e.g.*, Ph.D. and Ph D.

2.17.7 Units

The *Système International d’Unités*/International System of Units (SI) provides rules for consistent typesetting of quantities of units. Heldoorn [2007] provides a summary of these rules. The following is a summary of the main rules.

- The base unit symbols are printed in upright roman: g (gram), m (metre), t (tonne), Exceptions are unit symbols that are spelt in Greek and the symbols for inch, degrees, seconds, and so on.

Fill in the missing word. \\	Fill in the missing word.
Fill in the missing	Fill in the missing
.	.

Figure 2.11
The `\phantom` command

- The first letter of the unit symbol is uppercase if it is derived from a proper name: Å (Ångström), N (Newton), Pa (Pascal),
- The plural form of the base unit symbol is the same as the singular.
- The base unit symbols do not receive an end-of-abbreviation full stop.

Needless to say, it is important that you typeset quantities of units correctly and consistently. The hard way is doing it by hand. The easy way is doing it with L^AT_EX.

At the moment of writing the most popular package for specifying SI units is the `siunitx` package [Wright 2011].

- It provides support to configure how the SI units are typeset. For example, kg m s^{-1} , versus kg m s^{-1} , versus kg m/s , and so on.
- It provides commands to typeset quantities of units: `\SI[mode=text]{1.23}{\kilogram}` will give you 1.23 kg and `\SI{1.01}{\kilogram}` will typeset 1.01 kg in the default typesetting mode.
- The package provides macros to typeset lists of quantities in a given unit. For example `\SIlist{0.1;0.2;1.0}{\milli\metre}` gives you 0.1, 0.2 and 1.0 mm if the default typesetting mode is text. If you add the option `list-final-separator={, and~}` then you get 0.1, 0.2, and 1.0 mm.
- By default, unit symbols are typeset using the default math roman font but you can also use different fonts.

Discussing the entire `siunitx` package is beyond the scope of this book. The interested reader is referred to the package documentation [Wright 2011] for further information.

2.18 Phantom Text

Some commands don't typeset anything with ink but do affect the horizontal and vertical spacing. The following is the first of three useful versions.

``

This command “typesets” its argument using invisible ink. The dimensions of the box are the same as the dimensions required for typesetting `⟨stuff⟩`.

Figure 2.11 demonstrates how you use the command. The `\hphantom` and `\vphantom` commands are horizontal and vertical versions of the `\phantom` command. The following explains how they work.

`\hphantom{⟨stuff⟩}`

This is the horizontal version of the `\phantom` command. The command creates a box with zero height and the same width as its argument, `⟨stuff⟩`.

Figure 2.12

The center environment

```

\begin{center}
  Blah.\
  Blah blah blah.

  Blah blah blah blah blah
  blah blah blah blah blah
  blah blah blah blah blah.
\end{center}

```

Blah.
Blah blah blah.
Blah blah blah blah blah
blah blah blah blah blah
blah blah blah.

`\vphantom{<stuff>}`

This is the vertical version of the `\phantom` command. The command creates a box with zero width and the same height as its argument, `<stuff>`. It is especially useful for getting the right size for delimiters such as parentheses in mathematical formulae that span multiple lines. This is explained in more detail in Section 8.8.1. ☑

2.19 Alignment

This section studies three commands and two environments that change the text alignment. The first command centres text. The second and third command align text to the left and to the right. The first of the environments is the `tabular` environment, which typesets row-based content with horizontal alignment positions (columns). The last environment is the `tabbing` environment. This environment lets you define horizontal alignment (`tab`) positions and lets you position text relative to these alignment positions.

2.19.1 Centred Text

The `center` environment centres text. The example in Figure 2.12 demonstrates the environment. The example is inspired by Iggy Pop.

2.19.2 Flushed/Ragged Text

The `flushleft` environment and the `\raggedright` declaration typeset text that is aligned to the left. Likewise, the `flushright` environment and `\raggedleft` declaration typeset text that is aligned to the right. The example in Figure 2.13 shows the effect of the `flushleft` environment.

2.19.3 Basic tabular Constructs

The `tabular` environment typesets text with rows and alignment positions for columns. The environment also has siblings called `tabular*` and `array`. The `tabular*` environment works similar to `tabular` but it takes an additional argument that determines the width of the resulting construct. This environment is explained in Section 2.19.5. The

```

\begin{flushleft}
Blah.\
Blah blah blah.

Blah blah blah blah blah
blah blah blah blah blah
blah blah blah blah blah.
\end{flushleft}

```

Figure 2.13
The flushleft environment

array environment can only be used in math mode. The tabular and tabular* environments can be used in both text and math mode.

The remainder of this section introduces the tabular environment. This introduction should more than likely suffice for day-to-day usage. A more detailed presentation is provided in Section 2.19.5.

In its simplest form the tabular environment is used as follows.

```

\begin{tabular}[\langle global alignment \rangle]
               {\langle column alignment \rangle}
  \langle text \rangle & \langle text \rangle & \dots & \langle text \rangle \\
  \dots
  \langle text \rangle & \langle text \rangle & \dots & \langle text \rangle \\
  \langle text \rangle & \langle text \rangle & \dots & \langle text \rangle
\end{tabular}

```

The body of the environment contains a sequence of rows that are delimited by linebreaks (`\`). Each row is a sequence of alignments tab-delimited `\langle text \rangle`. The *i*-th `\langle text \rangle` in a row corresponds to the *i*-th column. The following explains the arguments of the environment:

`\langle global alignment \rangle`

This optional argument determines the vertical alignment of the environment. Allowed values are `t` (align on the top row), `c` (align on the centre), or `b` (align on the bottom row). The default value of this argument is `c`. ☑

`\langle column alignment \rangle`

This argument determines the column alignment and additional decorations. For day-to-day usage, the following options are relevant.

- l** This option corresponds to a left-aligned column.
- r** This corresponds to a right-aligned column.
- c** This corresponds to a centred column.
- p{`\langle width \rangle`}** This option corresponds to a top-aligned `\langle width \rangle`-wide column that is typeset as a paragraph in the “usual” way. Some commands such as `\` are not allowed at the top level.
- |** This option does not correspond to an actual column but results in additional decoration. It results in a vertical line drawn at at the “current” position. For example, if `\langle column alignment \rangle` is `l|cr` then there will be a vertical line separating the first two columns. Using this option is discouraged because the vertical lines usually distract. ☑

The tabular environment also defines the following commands,

Figure 2.14
Using the tabular environment

```

\begin{tabular}{l|crp{3.1cm}}
\hline
1 & 2 & 3
& Box me in,
& but not too
& tight, please.
\\ \hline
11 & 12 & 13 & Excellent.
\\ 111 & 112 & 113 & Thank you!
\\ \hline
\end{tabular}

```

1	2	3	Box me in, but not too tight, please.
11	12	13	Excellent.
111	112	113	Thank you!

which may be used inside the environment. You can only use these commands at the start of a row.

\hline

This command inserts a horizontal rule. The command may only be used at the *start* of a row.

\cline{<number₁>}{<number₂>}

This draws a horizontal line from the start of column $\langle \text{number}_1 \rangle$ to the end of column $\langle \text{number}_2 \rangle$.

\vline

This results in a vertical line. The command may only be used if the column is aligned to the left, to the right, or to the centre.

Figure 2.14 presents a simple example of the tabular environment. The example shows all alignments and the paragraph feature.

Note that line breaks are inserted automatically inside p-type columns. Line breaks are not allowed in columns aligned with l, r, or c.

Intermezzo. The column alignment option | and the commands \hline, \cline, and \vline are irresistible to new users. This may be because most examples of the tabular environment involve the option and these commands. It is understandable that new users want to repeat this, especially when they're not aware that using the option and the commands in moderation is better because the grid lines are dazzling and distracting. Chapter 6 provides some guidelines on how to design good tables.

Regular $m \times n$ tables with the same alignment in the same column are rare. The following command lets you join columns within a row and override the default alignment.

\multicolumn{<number>}{<column alignment>}{<text>}

This inserts $\langle \text{text} \rangle$ into a *single* column that is formed by combining the next $\langle \text{number} \rangle$ columns in the current row. The alignment of the column is determined by $\langle \text{column alignment} \rangle$. This command is especially useful for overriding the default alignment in column headings of a table. An example is presented in the next section.

2.19.4 *The booktabs Package*

The `booktabs` package adds some extra functionality to the tabular environment. The package discourages vertical grid lines. Using the `booktabs` package results in better looking tables.

The following are some of the package's features.

- It provides different commands for different rules.
- It provides different rules that may have different widths.
- It provides commands for temporarily/permanently changing the width of the rules.
- It has a command that adds extra line space.
- It is compatible-ish with the `colortbl` package, which is used to specify coloured tables.

The `booktabs` package provides the following commands. The first four commands take an option that specifies the width of the rule. The first four commands can only be used at the start of a row.

`\toprule[⟨width⟩]`
This typesets the full horizontal rule at the top the table. ☑

`\bottomrule[⟨width⟩]`
This typesets the full horizontal rule at the bottom of the table. ☑

`\midrule[⟨width⟩]`
This typesets the remaining full horizontal rules in the table. ☑

`\cmidrule[⟨width⟩]{⟨number1⟩-⟨number2⟩}`
This typesets a partial horizontal rule. The rule is supposed to be used in the middle of the table. It ranges from the start of column `⟨number1⟩` to the end of column `⟨number2⟩`. ☑

`\addlinespace[⟨height⟩]`
This command is usually used immediately after a line break and it inserts more vertical line space to the height of `⟨height⟩`. ☑

Figure 2.15 demonstrates how to use the `booktabs`-provided rule commands. The resulting output is presented in Figure 2.16. Notice that the inter-linespacing is much better than the output in Figure 2.14. Also notice the different widths of the rules.

2.19.5 *Advanced tabular Constructs*

Using basic tabular constructs usually suffices for day-to-day typesetting. This section explains the techniques that give you the power to typeset more advanced tabular constructs.

The following starts by presenting two addition column options. This is followed by some style parameters that control the default size and spacing of the tabular, `tabular*`, and `array` environments. The column options are as follows.

`*{⟨number⟩}{⟨column options⟩}`
This inserts `⟨number⟩` copies of `⟨column options⟩`. For example, `*{2}{lr}` is equivalent to `lrlr`. ☑

Figure 2.15

Input of booktabs package

```

\begin{tabular}[c]{lrrp{47mm}}
  \toprule \multicolumn{1}{r}{\textbf{Destination}}
           & \multicolumn{1}{r}{\textbf{Duration}}
           & \multicolumn{1}{r}{\textbf{Price}}
           & \multicolumn{1}{r}{\textbf{Description}}
\\ \midrule
  Cork City
  & 7 Days & \euro 300.00
  & Visit Langer Land. Price includes visits
    to Rory Gallagher Place and de Maarkit.
\\ Dingle
  & 8 Days & \euro 400.00
  & Have fun with Fungie.
\\ \bottomrule
\end{tabular}

```

Figure 2.16

Output of booktabs package. The input of this figure is listed in Figure 2.15. Clearly, booktabs rules rule.

Destination	Duration	Price	Description
Cork City	7 Days	€300.00	Visit Langer Land. Price includes visits to Rory Gallagher Place and de Maarkit.
Dingle	8 Days	€400.00	Have fun with Fungie.

@{<text>}

This is called an @-expression. It inserts <text> at the current position. This is useful if you want to add certain text or symbols at the given position. For example @{.} inserts a full stop at the current position.

L^AT_EX normally inserts some horizontal space before the first column and after the last column. It inserts twice that amount of space between adjacent columns. However, this space is suppressed if an @-expression precedes or follows a column option. For example, if <column alignment> is equal to @{}ll@{}l@{} then this suppresses the horizontal space before the first column, after the last column, and between the second and last column. The length \tabcolsep controls the extra horizontal space that is inserted. The value of the command is half the width that is inserted between columns.

A horizontal spacing command in an @-expression controls the separation of two adjacent columns. For example, @{\hspace{<width>}} inserts a horizontal <width>-wide space.

Finally, @-expressions may also adjust the default column separation. The \extracolsep{<width>} adds additional horizontal <width>-wide space between subsequent columns. *However*, additional width is never inserted before the first column. The \extracolsep{\fill} inserts the maximum possible amount of horizontal space. This is useful if you want to extend the width to the maximum possible width.

The columns in the second table in Figure 2.17 are spread out evenly with an @-expression. The third table adds the usual space to

```

\begin{tabular*}{3cm}{@{}lcr@{}}
 \toprule M & M & M \\\bottomrule
\end{tabular*}
\begin{tabular*}{3cm}
  {@\extracolsep{\fill}}%
  lcr%
  @{\hspace{0pt}}
  \toprule M & M & M \\\bottomrule
\end{tabular*}
\begin{tabular*}{3cm}
  {@\hspace{\tabcolsep}}%
  @\extracolsep{\fill}}%
  lcr%
  @{\hspace{\tabcolsep}}
  \toprule M & M & M \\\bottomrule
\end{tabular*}

```

M	M	M	M	M	M	M	M	M
---	---	---	---	---	---	---	---	---

Figure 2.17
Controlling column widths with an @-expression. The output is spaced out for clarity.

the start of the first and the end of the last column. The first table is added for comparison. ☑

The following commands control the default appearance of tabular, tabular*, and array environments.

\arraycolsep

This length is equal to half the default horizontal distance between adjacent columns in the array environment. This amount of space is also equal to the default horizontal space inserted before the first column and after the last column. ☑

\tabcolsep

This is half the default horizontal distance between adjacent columns in the tabular and tabular* environments. Again, this is equal to the default horizontal space that is inserted before the first column and after the last column. ☑

\arrayrulewidth

This length is the width of the lines resulting from a | in the <column options> argument and the lines resulting from the commands \cline, \hline, and \vline. ☑

\doublerulesep

This is the distance between two adjacent lines resulting from a || in the <column options> argument or two adjacent lines resulting from the \hline command. ☑

\arraystretch

This command determines the distance between successive rows. It defaults to 1 and “multiplying” it by x results in rows that are x times further apart. So, by redefining this command to 0.50 you halve the row distance. Redefining commands is explained in Chapter 11. ☑

Figure 2.18

The tabbing environment

<code>\begin{tabbing}</code>	<code>From \=here to \=there \\</code>	From here to there
	<code>\>and \>then\\</code>	and then
	<code>\>\>all\\</code>	all
	<code>\>the \>way\\</code>	the way
	<code>back \>to \>here.</code>	back to here.
	<code>\end{tabbing}</code>	

2.19.6 The tabbing Environment

The tabbing environment is useful for positioning material relative to user-defined alignment positions. The remainder of this section describes some basic usage of the environment. The reader is referred to [Lamport 1994, pages 201–203] for more detailed information.

The tabbing environment can only be used in *paragraph mode* (the “usual mode”). It produces lines of text with alignment in columns based upon *tab positions*.

<code>\=</code>	Defines the next tab (alignment) position.	☑
<code>\\</code>	Inserts a line break and resets the next tab position to the value of <code>left_margin_tab</code> .	☑
<code>\kill</code>	Throws away the current line but remembers the tab positions defined with <code>\=</code> .	☑
<code>\+</code>	Increments <code>left_margin_tab</code> .	☑
<code>\-</code>	Decrements <code>left_margin_tab</code> .	☑
<code>\></code>	Move to the next tab stop.	☑

Figures 2.18 and 2.19 present two examples of the tabbing environment. The examples do not demonstrate the full functionality of the environment.

2.20 Language Related Issues

As suggested by its title, this section is concerned with language related issues. The remaining three sections deal with hyphenation, foreign languages, and spelling.

2.20.1 Hyphenation

\LaTeX 's (\TeX 's really) automatic hyphenation is second to none. However, sometimes even \TeX gets it wrong. There are two ways to overcome such problems.

- The command `\-` in a word tells \LaTeX that it may hyphenate the word

```

\begin{tt}\begin{tabbing}
AAA\=AAA\=AAA\=AAA \kill
FUNC euc( INT a,          FUNC euc( INT a, INT b ): INT
          INT b ): INT \\  BEGIN
BEGIN \+ \\              WHILE (b != 0) DO
  WHILE (b != 0) DO \\    BEGIN
  BEGIN \+ \\              INT rem = a MOD b;
    INT rem = a MOD b; \\  a = b;
    a = b; \\              b = rem;
    b = rem; \- \\        END
  END \\                  RETURN a;
  RETURN a; \- \\        END;
END;
\end{tabbing}\end{tt}

```

Figure 2.19
Advanced tabbing

```

\usepackage[dutch,british]{babel}
:
\selectlanguage{dutch}
% Dutch text here.
  Nederlandse tekst hier.

\selectlanguage{british}
% Engelse tekst hier.
  English text here.

```

Figure 2.20
Using the babel package

at that position.

Er\~go\~no\~mic has three hyphenation positions. L^AT_EX Usage

- o Specifying the same hyphenation patterns is messy and prone to errors. Using the `\hyphenation` command is a much cleaner solution. This command takes one argument, which should be a comma-separated list of words. For each word you can put a hyphen at the (only) possible, desired, or allowed hyphenation positions. You may use the command several times. The following is an example.

`\hyphenation{fortran,er-go-no-mic}` L^AT_EX Usage

2.20.2 Foreign Languages

The `babel` package supports multi-lingual documents. The package supports proper hyphenation, switches between different languages in one single document, definition of foreign languages, commands that recognise the “current” language, and so on. Figure 2.20 provides a minimal example. Rik Kabel kindly informed that X_YL^AT_EX users use the `polyglossia` package instead of `babel`. One of the advantages of the `polyglossia` package is that it automatically loads the `bidi` package when bi-directional scripts are used.

2.20.3 *Spell-Checking*

L^AT_EX does not support automatic spell-checking. Note that spell-checking isn't trivial anyway because commands may generate text. Text may come from external files, so make sure you spell-check your bibliography files.

However, most modern Integrated Development Environments (IDES) have a spell checker. The `ispell` program, which can be run from the command line, has a L^AT_EX spell-check mode. The `-t` flag tells the command that the input is L^AT_EX.

```
$ ispell -l -t -S input.tex | sort -u
```

Unix Session

PART III

**Tables,
Diagrams,
and
Data Plots**

Picture omitted to keep size of .pdf small.

Oil and charcoal on canvas (24/01/08), 132 × 213 cm
Work included courtesy of Billy Foley
© Billy Foley (www.billyfoley.com)

PART IV

**Mathematics
and
Algorithms**

Picture omitted to keep size of .pdf small.

Oil paint and charcoal on canvas (05/09/09), 152 × 213 cm
Work included courtesy of Billy Foley
© Billy Foley (www.billyfoley.com)

PART V

Automation

Picture omitted to keep size of .pdf small.

Oil paint and charcoal on canvas (17/06/09), 152 × 213 cm
Work included courtesy of Billy Foley
© Billy Foley (www.billyfoley.com)

PART VI

Miscellany

Picture omitted to keep size of .pdf small.

Oil and charcoal on canvas (06/10/10 no 2), 64 × 91 cm
Work included courtesy of Billy Foley
© Billy Foley (www.billyfoley.com)

CHAPTER 17

Using L^AT_EX on Windows

THIS CHAPTER EXPLAINS how to install a free and widely available L^AT_EX distribution called T_EX Live on Windows, how to use a widely used L^AT_EX IDE called TeXworks, and a B_IB_TE_X IDE called JabRef.

T_EX Live is easy to install and use. For example, this book was typeset with a standard T_EX Live installation without any special configurations. Another advantage of using T_EX Live is that it works on Windows, on Unix, and on the Mac. This is also one of the reasons for choosing the L^AT_EX and B_IB_TE_X IDEs. However, the IDEs were also chosen because they are easy to use.

The remainder of this chapter starts by explaining how to uninstall your previous T_EX Live installation and how to install T_EX Live. This is followed by some sections explaining how to use TeXworks and JabRef. The last section explains how to install class and package files.

17.1 Removing Your Previous Installation

There should not be any reason to uninstall your previous T_EX Live installation. However, if you are stuck for disk space removing the previous installation may help. Notice that you may need administrator rights if you want to remove the previous installation.

Uninstalling the previous installation is done by running the command `tlmgr uninstall` from the command line. To do this open the Start menu, select Run, and enter command. In the window that opens you can type in commands from the command line. You should type in the command `tlmgr uninstall`:¹

```
C:\> tlmgr uninstall
```

Windows Usage

17.2 Installing T_EX Live

This section explains how to install T_EX Live. If you have internet access, you can download a T_EX Live installer from <http://tug.org/texlive/acquire-netinstall.html>. If you don't have internet access or if internet access is slow, you can install T_EX Live from a T_EX Collection Digital Versatile Disk (DVD). You may get a copy of the

¹The text `C:\Users\user>` in the example is the *prompt*, which is output by the Operating System (OS) when it's ready to accept a command. Prompts differ from system to system and from user to user, so your prompt may be different.

DVD from a friend, from a T_EX user group, or (if you have it) from your local IT support. A list of all T_EX user groups may be found at <http://www.tug.org/usergroups.html>. Installing from DVD is similar to installing from the internet. To simplify the presentation, this section assumes you have internet access.

17.2.1 Proxy Configuration

To install T_EX Live over the internet you need internet access. If access to the internet is via a proxy then you must tell the installation program about the address of the proxy. You do this by creating an environment variable that holds the value of the proxy's address. To create the environment variable you do the following. (You may need administrator rights to do this.)

1. Left click Main Menu.
2. Right click My Computer.
3. Select Properties.
4. Select Advanced.
5. Click the Environment Variables button.
6. In the System Variables section click the New button. This should open the New System Variable dialogue box.
 - a. Enter the text `http_proxy` in the Variable Name text box.
 - b. Enter the URL and the port number of your proxy in the Variable Value text box. For example `http://http-proxy:8080` but this may depend on your computer's configuration.
 - c. Click the Ok button until you're done.

17.2.2 Downloading the Installer

The recommended method for installing T_EX Live is using the *network installer*, which downloads the T_EX Live distribution as part of the installation process. To download the network installer, go to <http://tug.org/texlive/acquire-netinstall.html>, click on the *install-tl.zip* link, and save the installer on your desktop.

17.2.3 Running the Installer

The main installation process is not much more difficult than downloading the installer. The following are the main details.

1. Rest your mouse pointer over the installer icon on your desktop. Right click and select `extract all`. Select all the default options to finish the extraction process. After this process you should have a folder called `install-tl-⟨number⟩`. The `⟨number⟩` corresponds to the year and the version of the installation.
2. Go to the installation folder by double clicking `install-tl-⟨number⟩`.
3. Double click `install-tl.bat` (it may appear as `install-tl`) to start

the installation process. Accept all default configurations to complete the installation.

The T_EX Live installation process should have created a sub-menu called TeX Live (year) under Start→All Programs, where (year) is the year of the T_EX Live distribution. The sub-menu contains some useful utility programs, some of which are explained further on.

Except for some minor configuration, which is explained in the next section, you are now done with the installation process.

17.2.4 Minor Configuration

Usually, T_EX Live does a pretty good job when it comes to selecting the defaults. However, it may get things wrong when it comes to the default paper size, which is set to A4. If you require an 8.5 × 11 inches paper size, the easiest way to make this the default paper size is running the command `tlmgr paper letter` from the command line. There is also a Graphical User Interface (GUI) for `tlmgr` but it is not explained to simplify the presentation.

Run `tlmgr` from the command line works as before: Open the Start menu, select Run, and enter command; in the window that opens type in the command `tlmgr paper letter`:

```
C:\Users\user> tlmgr paper letter Windows Usage
```

17.2.5 Testing the Installation

At this stage it is a good idea to test the installation. To test your installation you could create a L^AT_EX input file and process it with `pdflatex`. However, it may be easier to compile one of the files that come with T_EX Live. For example, you should be able to compile the file `small2e.tex` by executing the command `pdflatex small2e.tex` from the command line.

```
C:\Users\user> pdflatex small2e.tex Windows Usage
```

Thanks to the T_EX Live Team, the test passes with flying colours.

17.3 First Steps with TeXworks

TeXworks is a L^AT_EX IDE that is based on an award-winning L^AT_EX Mac IDE called TeXShop. TeXworks has a simple user interface, is easy to use and is installed as part of T_EX Live. TeXworks also works on Unix and on the Mac (as TeXShop). These are the main reasons why TeXworks is the only L^AT_EX IDE that is explained in this chapter.

This section explains how to create and compile the L^AT_EX input in Figure 17.1. The L^AT_EX input file depends on a tiny bibliography file called `LAF.bib`, which is listed in Figure 17.2. To save time, you may download both files from <http://cswb.ucc.ie/~dongen/LAF/>

Figure 17.1
 \LaTeX input for bibliography example

```

\documentclass[11pt]{book}
\usepackage[style=authoryear,
            block=space,
            language=british]{biblatex}
\renewcommand*{\bibopenparen}{[]}
\renewcommand*{\bibcloseparen}{]}
\renewcommand*{\bibnamedash}{\rule[0.48ex]{3em}{0.14ex}\space}
\addbibresource{LAF}

\begin{document}
  \chapter{Philip Glass}
  \begin{refsection}
    Philip Glass' \emph{Analog}~\parencite{Analog} \ldots
  \end{refsection}
  \chapter{Steve Reich}
  \begin{refsection}
    Steve Reich's \emph{Come Out}~\parencite{Come@Out} \ldots
    \emph{Music for 18~Musicians}~\parencite{18@musns} \ldots
  \end{refsection}
  \printbibliography[section=1,title=Philip Glass Discography]
  \printbibliography[section=2,title=Steve Reich Discography]
\end{document}

```

Figure 17.2
 \BibTeX input for bibliography example

```


@Misc{Analog,
  author = {Glass, Philip},
  title  = {Analog},
  year   = {2006} }
@Misc{18@musns,
  author = {Reich, Steve},
  title  = {Music for 18~Musicians},
  year   = {1976} }
@Misc{Come@Out,
  author = {Reich, Steve},
  title  = {Come Out},
  year   = {1966} }

```

Extras/bibliographies.tex and <http://csweb.ucc.ie/~dongen/LAF/Extras/LAF.bib>.

Start by running \TeX works and by loading the input program. The following explores the most important aspects of the \TeX works GUI.

- The \TeX works GUI is shown in the picture on the left of Figure 17.3.
- The green circle with the grey triangle in it is the *typesetting button*.
- To the right of the typesetting button is a drop-down list, which is called the *typesetting engine list*. You use it to select the current *typesetting engine*, which “typesets” your document.
- The typesetting engine is run when you click the typesetting button.

**Figure 17.3**

Setting the typesetting engine. The picture on the left shows TeXworks with pdfTeX as the current typesetting engine. The picture on the right shows how the typesetting engine is changed to pdfLaTeX by selecting it from the drop-down list to the right of the typesetting button.

The drop-down list always shows the current typesetting engine. In the picture on the left of Figure 17.3 the typesetting engine is pdfTeX.

- There are different typesetting engines: pdfLaTeX, BibTeX, MakeIndex, pdfTeX, For example, when pdfLaTeX is the typesetting engine, pdf_latex is used to typeset the document, when BibTeX is the typesetting engine, bib_tex is used to “typeset” the document, and so on. Note that typesetting engines are defined at the TeXworks level: they drive executable programs. For example, the pdfLaTeX engine drives the pdf_latex executable.
- You may change the current typesetting engine by selecting it from the typesetting engine list. This is shown in the picture on the right of Figure 17.3, which selects pdfLaTeX.

You now know the basics of the TeXworks GUI. You might as well start using it:

1. This book uses a pdf_latex philosophy, so make sure you pdfLaTeX is selected in the typesetting engine list.
2. Proceed by typesetting the document, which you may do by clicking the typesetting button.
3. When you click the button, this should create your output document and should pop up a pdf viewer that displays the output document. Here it is assumed you downloaded the input program and didn't change it. If you have errors, then you may have to resolve the errors and typeset the document until all errors are gone.

Congratulations. You have just overcome the first obstacle on the short path of becoming a TeXworks expert.

On closer inspection the output document isn't perfect. For example, the citation commands in the text only list the logical citation labels, and there is no bibliography. The following section explains how to resolve these problems.

17.4 Creating Bibliographies with TeXworks

This section explains how to create proper bibliographies in combination with TeXworks. We shall continue with the example from the previous section. Make sure you have saved the BibTeX input from Figure 17.2 in a file called LAF.bib. It is recommended you download the BibTeX input from <http://csweb.ucc.ie/~dongen/LAF/Extras/LAF.bib>.

17.4.1 Creating One Single Bibliography

As explained in the first chapter, running pdf`latex` alone cannot guarantee a consistent bibliography. If you want to create your bibliography with BibTeX, you also have to run `bibtex`. In this section you learn how to create a bibliography with TeXworks. For simplicity, we shall continue the example from the previous section. Start TeXworks, load the example, and typeset it once with the pdfLaTeX engine.

Most documents have only one bibliography. Remember from Chapter 1 that you compile such documents, by first running pdf`latex`, then running `bibtex`, and then running pdf`latex` two more times. You already know how to run pdf`latex` from within TeXworks. If only you could execute `bibtex` from within TeXworks ... Fortunately, this is possible. You can run `bibtex` by typesetting your document with the BibTeX engine. You see why TeXworks is easy?

1. Start by making BibTeX your typesetting engine.
2. Execute `bibtex` by clicking the typesetting button.
3. Continue by making pdfLaTeX your typesetting engine again.
4. Complete the process by typesetting your document two more times. You do this by clicking the typesetting button twice.


For documents with one bibliography, the previous procedure is enough to get perfect bibliographies. Unfortunately, our L^AT_EX input file has more than one bibliography. When you typeset such documents with the BibTeX engine, TeXworks only runs `bibtex` on one auxiliary bibliography file. In the next section we shall configure TeXworks so it will run `bibtex` on all auxiliary bibliography files.

17.4.2 Creating Several Bibliographies

As explained in the previous section the BibTeX typesetting engine only runs `bibtex` on one auxiliary bibliography file. In this section we shall configure the engine so that `bibtex` is executed for each relevant file. After the configuration the BibTeX typesetting engine should work correctly for any number of bibliographies.

To configure the BibTeX typesetting engine, you do the following.

1. Select Edit→Preferences. This pops up the Preference menu.

**Figure 17.4**

Configuring TeXworks for multiple bibliographies. The TeXworks Preference menu on the left pops up when you click edit→preferences and then select the Typesetting tab. Selecting BibTeX and clicking Edit pops up the menu on the right. This is where you configure the BibTeX engine. The Program text field determines the program that is executed for the BibTeX engine, and the Arguments text field determines its argument.

2. Proceed by selecting the Typesetting tab. This activates the Typesetting Menu. This is shown on the left of Figure 17.4.
3. In the Processing Tools list select BibTeX. This pops up the Tool Configuration menu for the BibTeX typesetting engine. This is shown on the right of Figure 17.4.
4. The Program text box in the Tool Configuration menu determines the program that TeXworks executes when you typeset your document with the BibTeX engine. Enter `bibtex-all`; we shall implement this user-defined script later.
5. The Arguments text box in the Tool Configuration menu determines which arguments are passed to our user-defined script. Enter `$basename`.
6. Accept the current configuration by repeatedly clicking the Ok buttons until the Preference menu is gone.
7. At this stage, you're almost done. All that's left is implementing the user-defined script, which should have the following commands. You may download the script from <http://csweb.ucc.ie/~dongen/LAF/Extras/windows/bibtex-all.bat>. (The 1 in %1*.aux is the digit one.)

```
for %f in (%1*.aux) do (
    bibtex %~nf
)
```

8. Save the script as `bibtex-all.bat` in a folder that is in your PATH, and make sure the script is executable.

You should now be able to create your bibliographies by typesetting your document once with the BibTeX typesetting engine and twice with the pdfLaTeX typesetting engine.

17.5 Creating Indexes with TeXworks

In this section we shall create an output document with indexes. We shall do this using the L^AT_EX input that is depicted in Figure 17.5. You

Figure 17.5 \LaTeX input for indexes example

```

\documentclass[llpt]{article}
\usepackage{multind}

\makeindex{programs}
\makeindex{authors}
\begin{document}
  Knuth\index{authors}{Knuth} is the author of
  \TeX\index{programs}{TeX@TeX}.

  \printindex{programs}{Index of Programs}
  \printindex{authors}{Index of Authors}
\end{document}

```

may download the input from <http://csweb.ucc.ie/~dongen/LAF/Extras/indexes.tex>.

Creating the indexes is done by typesetting the document with the MakeIndex engine. Unfortunately, this will only create one proper index, so you have to configure the MakeIndex engine. You may do this with a similar technique as the technique for configuring the BibTeX typesetting engine. The following explains the configuration process.

1. Select Edit→Preferences. This activates the Preference menu.
2. Proceed by selecting the Typesetting tab.
3. In the Processing Tools list select MakeIndex and click the Edit button. This should activate the Tool Configuration menu for the MakeIndex typesetting engine.
4. Enter `makindex-all` in the Program text box; we shall implement this user-defined script later.
5. There is no need to enter anything in the Arguments text box. The reason for this is that the names of the index files don't depend on the \LaTeX document name, so `makeindex` has to process all `.idx` files.
6. Accept the current configuration by repeatedly clicking the Ok buttons until the Preference menu is gone.
7. Implementing the user-defined script completes the configuration. The following is the script. You may download the script from <http://csweb.ucc.ie/~dongen/LAF/Extras/windows/makeindex-all.bat>.

```

for %%f in (*.idx) do (
    makeindex %%~nf
)

```

8. Save the script as `makeindex-all.bat` in the same folder as `bibtex-all.bat`.

You should now be able to create your indexes by (1) typesetting your document with the pdfLaTeX typesetting engine, (2) typesetting it with the MakeIndex typesetting engine, and (3) typesetting it two more times with the pdfLaTeX typesetting engine.

17.6 The LaTeXmk Typesetting Engine

The previous two sections explained how to configure TeXworks for multiple bibliographies and multiple indexes and how to compile your document in a “traditional” manner. A fairly recent development is compiling your documents with *latexmk*, which is equivalent to a make script for L^AT_EX.

At the time of writing this chapter, *latexmk* was sufficiently advanced that it could typeset most documents automatically. You just run `latexmk -pdf` on your L^AT_EX source file, and the software will execute `pdflatex`, `bibtex`, and `makeindex` on all relevant files until it reaches a fixpoint (until there are no more changes). Needless to say, using *latexmk* is much easier than running several different programs by hand. The only disadvantage of the *latexmk* approach is that *latexmk* may take a bit longer. Further information about *latexmk* may be found on <http://www.phys.psu.edu/~collins/software/latexmk-jcc/>.

TeXworks also has a LaTeXmk typesetting engine. As suggested by the name, the engine compiles your input document with *latexmk*. If you are the kind of person that wants to do things the easy way, then this may be the typesetting engine for you.

17.7 Bibliography Management with JabRef

JabRef [*JabRef*] is an open source BIB_TE_X IDE. JabRef requires Java Virtual Machine (JVM) version 1.5 or newer and should run on any machine that has a JVM running. If you don't have a JVM on your machine, visit the JabRef Frequently Asked Question (FAQ) at <http://jabref.sourceforge.net/faq.php> for instructions on how to best install it.

JabRef has an advanced BIB_TE_X editor, a search engine that lets you search for patterns in the bibliography, an import facility for various other bibliography formats, automatic key generation, and a search facility that lets you search Search Medline, Citeseer, IEEEExplore and arXiv on line.

The remainder of this section is a very short introduction to JabRef, which should be just enough to create a new BIB_TE_X file and edit it. This should be enough to get started; you may learn more about JabRef from its built-in help function.

17.7.1 Installing JabRef

Installing JabRef is easy. To install JabRef, visit the JabRef download page at <http://jabref.sourceforge.net/download.php> and click one of the download buttons for the latest stable version. Click on the link `JabRef-<number>-setup.exe` and save it on your desktop. Go to your desktop and double-click on `JabRef-<number>-setup.exe` to start the installation process. Accept all the defaults.

When the installation process is finished, you should have a JabRef icon on your desktop and a JabRef entry in the Start→All Programs

Figure 17.6
Sample JabRef bibliography
input

```

@Book{Knuth:1990,
  title      = {The {\TeX}book},
  publisher  = {Addison\textendash Wesley},
  year      = {1990},
  author    = {Knuth, Donald E.},
  isbn     = {0-201-13447-0},
  url      = {http://www.ctan.org/tex-archive/systems/knuth/tex/}
}
@Article{Knuth:78,
  author    = {Knuth, Donald E.},
  title     = {The Average Time for Carry Propagation},
  journal   = {Indagationes Mathematicae},
  year     = {1978},
  volume   = {40},
  pages    = {238-242}
}
@Book{Lamport:94,
  title     = {{{\LaTeX}: \emph{A Document Preparation System}}},
  publisher = {Addison\textendash Wesley},
  year     = {1994},
  author   = {Lamport, Leslie},
  isbn    = {0-021-52983-1}
}

```

menu. Further more, all your BIBTEX files should be associated with JabRef so double-clicking any BIBTEX file should open it with JabRef.

17.7.2 Using JabRef

This section explains how to create and modify a BIBTEX file with JabRef. It uses the tiny BIBTEX file that is depicted in Figure 17.6. You may download the file from <http://csweb.ucc.ie/~dongen/LAF/Extras/JabRef.bib> and save it as `JabRef.bib`.

Start JabRef and open the bibliography database `JabRef.bib`. You should now see the picture at the top of Figure 17.7. The IDE is rather intuitive and shows the different kinds of entries in the BIBTEX file: there are two books and one article. The globe on the left side of the entry for the `TeXbook` corresponds to the `url` field in the BIBTEX file. Clicking on the globe leads to the URL in the `url` field. The BIBTEX keys are listed in the column `Bibtexkey`. If this column is bit too far to the right to your liking, then you can drag it to a different position. This is shown in the picture at the bottom of Figure 17.7. Other columns may be repositioned similarly.

To create a new entry for an article, select `BibTeX`→`New entry`, and select `Article` as the entry type. Clicking the green plus icon is an alternative selecting `BibTeX`→`New entry`. In the menu that pops up, enter the fields for some real or fictional article. The picture at the top of Figure 17.8 shows the result of filling out the fields required




Figure 17.7
JabRef IDE. The picture on the top shows the original IDE. In the picture on the bottom, the Bibtexkey column is dragged to just before the Owner column.





Figure 17.8
Creating a new BibTeX entry. The figure at the top shows the Required fields tab with filled out text fields for the required entries of an article. The figure on the bottom shows the Optional fields tab with the filled out text field for the number of the journal.



fields Author, Title, Journal, Year, Volume, and Pages. You may fill in the BibTeXkey field with an explicit key. If you're stuck for a choice, JabRef will generate a key for you if you click the magic wand icon, which is to the left of the Title text field.

If your article is in a journal that has a number, you have to fill out the optional Number entry. You may do this by clicking the Optional fields tab and entering the number in the Number text field. The picture at the bottom of Figure 17.8 shows the result. You may save the current BibTeX database, including the new article entry, by selecting File→Save database or by clicking the (single) floppy disk icon.

17.8 Installing Classes and Packages

This section explains the two basic class and package installation techniques in TeX Live. The first and preferred technique uses the tlmgr program, which is provided by TeX Live. The second technique is “installing by hand,” which is prone to errors.

Installing class and package files is impossible unless you know a little bit about how TeX Live organises its files, and how TeX Live executables locate these files. The first three sections provide a quick introduction to the required background. The last two sections explain how to install class and package files. Throughout, the word package is a synonym for class or package.

17.8.1 The TeX Directory Structure

TeX Live distributions are huge and with the current technology of operating systems it is impossible to quickly locate a file that is located underneath some directory. What is more, TeX Live distributions cannot guarantee unique file names. For example, an auxiliary file called `aux.tex` may occur in more than one directory.

The TeX Users Group (TUG) Working Group on a TeX Directory Structure TWG-TDS [2004] defined a TeX Directory Structure (TDS), which is specifically designed to overcome problems related to the efficient location of files in a TeX distribution. TeX Live has adopted the TDS and many classes and packages assume an underlying TDS.

Note that a TDS is a property of a directory and several directories may have a TDS. For example, if you accept all defaults when you install TeX Live on Windows, then the global TeX Live files are in the directory `%SYSTEMDRIVE%\texlive\<year>`, where `<year>` is the year of the TeX Live distribution. At the directory's root is a large directory called `texmf-dist`, which has a TDS. Effectively, this is where TeX Live keeps most of its class and package files. Likewise, TeX Live assumes the existence of a user directory called `%USERPROFILE%\texmf`, which should also have a TDS.

Within a TDS-compliant directory, each type of file is expected in a specific place. Figure 17.9 depicts some of the aforementioned TDS `texmf-dist`. At the root level the figure shows the directories `bibtex`, `doc`, `fonts`, and `tex`. As suggested by the names, the directory `bibtex`




Figure 17.9 T_EX directory structure (TDS). The directory `texmf-dist` at the root of the depicted directory tree is where T_EX Live keeps its files. The directories inside `texmf-dist`, form a hierarchical structure that is common to other TDS-compliant directories. At the top level the directories `bibtex`, `doc`, `fonts`, and `tex` have a prescribed structure. For example, the directory `texmf-dist\tex\latex` has one directory for each standard installed package. The package files are then organised inside their directory. For example, the `url` package file is located in the file `tex\latex\url\url.sty` inside `texmf-dist`. The files for the `siunitx` package are located in the subdirectory `tex\latex\siunitx\siunitx.sty`.

is for B_IB_TE_X related files, `doc` is for documentation, `fonts` is for font files, and `tex` is for T_EX files. L^AT_EX files should be put in the directory `dirtex/latex`, which should have a subdirectory for each package. The figure shows two such package directories: `siunitx` and `url`. The main purpose of each package directory is storing “its” package files.

17.8.2 Updating an `ls-R` Database

When a T_EX Live executable such as `pdflatex` has to locate a package, it uses a library called `kpathsea` [Berry, Weber, and Hoekwater 2011], which uses several different techniques to locate the package. One of these techniques is looking up the package location in a plain-text `ls-R database`, of which there may be several.

The name of an `ls-R` database is always the same: `ls-R`. Because the name of each `ls-R` database is unique, there can be no more than one `ls-R` database in a given directory. We say that an `ls-R` database is *rooted* in the directory that it is in. Likewise, we say that a directory is the *root* of its `ls-R` database. The main purpose of an `ls-R` database

is to store the locations of classes, packages, and other files in the database's root directory and descendant directories.

Remember that you may install a package with `tlmgr` or by hand. When `tlmgr` installs a package, `tlmgr` updates all the relevant `ls-R` databases. When a package is installed in one of these `ls-R` directories (or one of its descendant directories), this usually requires updating the `ls-R` database. You may do this by executing the following command.

```
C:\> texhash <root directory>
```

Windows Usage

Here `<root directory>` is the root directory of the `ls-R` database. If `root directory` is large, running the command may take a while. Note that you need write access to the database, so you may need administrator access to do this.

17.8.3 How `kpathsea` Finds its Files

As explained earlier on in this chapter, \TeX Live executables delegate the task of locating classes, packages, and other files to the `kpathsea` library [Berry, Weber, and Hoekwater 2011]. This section explains this process in more detail. To simplify the presentation, this section only discusses how `kpathsea` locates package files. The process for \LaTeX (`.tex`), class (`.cls`), and other types of files is similar [Berry, Weber, and Hoekwater 2011].

When `pdf \LaTeX` formally asks `kpathsea` for the location of a given package called `<package>`, the library starts by constructing a *search path*. Berry, Weber, and Hoekwater [2011, section 3.2] explains how the search path is constructed.

A `kpathsea` search path is a list of colon-separated *path elements*. Each path element consists of a single annotated directory. The annotation determines how the directory should be searched for `<package>`.

As expected, `kpathsea` processes the path elements in the search path from left to right until it finds the location of `<package>` or fails.

1. When `kpathsea` processes the next path element, it starts by extracting the directory, `<directory>`, from the path element.
2. If one of the prefixes of `<directory>` is the root of an `ls-R` database, then `kpathsea` tries to look up the location of `<package>` in that `ls-R` database [Berry, Weber, and Hoekwater 2011, page 27]. If this operation succeeds, then `kpathsea` returns the resulting location. (Berry, Weber, and Hoekwater [2011] implies that there should be no more than one `ls-R` database along any path leading from any directory to any leaf directory. Furthermore, the name of the `ls-R` database should be in the internal `kpathsea` variable `TEXMFDBS`. This was confirmed by Karl Berry in private communication.)
3. Otherwise, `kpathsea` considers the annotation of the path element.
4. If the path element is of the form `!!<directory>`, `kpathsea` stops processing the path element.
5. If the path element is of the form `<directory>//`, `kpathsea` completes

- processing the path element by searching \langle directory \rangle recursively for \langle package \rangle .
6. If the path element is of the form \langle directory \rangle , kpathsea completes processing the path element by searching \langle directory \rangle without recursion. It is assumed the directory has a TDS.
 7. (Other path element forms are not allowed.)

The following command outputs the kpathsea search path for pdf_latex and style files.

```
C:\> kpsewhich -programe pdflatex -show-path .sty Windows Usage
```

When you run this, many of the path elements in the output have directories that are annotated with the !! prefix. If you install a new package in one of these directories (or descendant directories thereof) then the ls-R database in that directory *must* be updated. If you forget updating the database, the package may never be found.

17.8.4 Installing Packages with t_lm_gr

As already mentioned, the t_lm_gr program is provided as part of T_EX Live. The main purpose of t_lm_gr is updating and installing packages and classes that are part of T_EX Live. The program can also update itself. You don't need administrator access to use the program.

If you want to install a class or package that is part of T_EX Live then installing them with t_lm_gr is by far the easiest. Not only will t_lm_gr install the class or package for you but it will also update any relevant ls-R database. The following is how you install classes and packages with t_lm_gr from the command line. There is also a t_lm_gr GUI but this is not explained here.

- t_lm_gr install \langle names \rangle**
 This installs the classes and packages in the list \langle names \rangle . There is no need to add extensions in \langle names \rangle . ☑
 There is also a t_lm_gr GUI but this is not explained here.
 The following are some other useful kpathsea options for day-to-day use.
- t_lm_gr -help**
 This provides a short explanation of how to use t_lm_gr. For complete information, visit <http://tug.org/texlive/doc/tlmgrr.html>. ☑
- t_lm_gr update \langle names \rangle**
 This updates the classes and packages in the list \langle names \rangle . There is no need to add extensions in \langle names \rangle . ☑
- t_lm_gr update --all**
 This updates all classes and packages. ☑
- t_lm_gr update --self**
 This updates t_lm_gr itself. This option may be required if your T_EX Live distribution is too old. ☑
- t_lm_gr update --self --all**
 This updates t_lm_gr and all classes and packages. ☑
 The t_lm_gr program can also make backups, restore backups, and

lots of other things. The package documentation at <http://tug.org/texlive/doc/tlmgr.html> provides further information.

17.8.5 *Installing Packages by Hand*

The previous section showed that installing packages with `tlmgr` is easy. Unfortunately, not all packages are supported by \TeX Live, some have to be installed by hand.

Installing classes and packages by hand requires a bit more work than installing with `tlmgr`. Fortunately, it is not much more difficult if you install them in your *local texmf tree*—a \TeX DS that is reserved for user-defined class and package files [Berry 2011, page 11].

You may get the location of your (local) `texmf` tree by executing the command `kpsewhich var-value=TEXMFHOME` from the command line. By default \TeX Live uses `%USERPROFILE%\texmf` for your `texmf` tree.

Remember from the second last section that the command `kpsewhich -programe pdflatex -show-path .sty` shows the search path for package files. If \TeX Live is installed with all the defaults, this command should list your local `texmf` tree in a path element that is suffixed with `//` annotation. Recall that the `//` suffix means that `kpathsea` searches the directory recursively. If all you have to do is installing a single file then creating a subdirectory for the package in your local `texmf` tree and putting the file in that directory should be enough. If the package you're installing is based on a \TeX DS then unpacking the files in the root of your local `texmf` tree should suffice. After this you may, but this is not required update the `ls-R` database at the root of your local `texmf` tree. (Remember that you may do this with the command `texhash`.)

Unfortunately, not all packages are provided as a \TeX DS and you may have to uncompress the files, build the package documentation, move all files to their destination directories, and update the `ls-R` database. The following shows how to do this for a package called `(package)`.

1. Create a temporary directory. Download, save, and if necessary extract the package files in this temporary directory.
2. Usually there is a `.ins` file. If there is, run `pdflatex` on it.
3. If there is a `.dtx` file then you must create the class or package documentation. You do this by running `pdflatex` once or twice on the `.dtx` file.
4. What remains is moving the files to the correct location in the local `texmf` tree. In the following it is assumed the local `texmf` tree is in the default \TeX Live location: `%USERPROFILE%\texmf`. Start by creating the destination directories for the \LaTeX files and for the documentation.

```
C:\> mkdir %USERPROFILE%\texmf\tex\doc\<(package)
C:\> mkdir %USERPROFILE%\texmf\tex\latex\<(package)
```

5. Move all \LaTeX files to the proper destination.

Extension	Destination in %USERPROFILE%\texmf\fonts
.afm	afm\ <vendor>\\<="" td=""> </vendor>
.map	map\pdftex\ <vendor>< td=""> </vendor><>
.pfb	type1\ <vendor>\\<="" td=""> </vendor>
.tfm	tfm\ <vendor>\\<="" td=""> </vendor>
.ttf	truetype\ <vendor>\\<="" td=""> </vendor>
.vf	vf\ <vendor>\\<="" td=""> </vendor>

Table 17.1

TeX Live font directories. The first column lists the extension of the font files. The second column lists the destination directory for these files. The destination is relative to %USERPROFILE%\texmf\fonts .

```
Windows Usage
C:\> move *.tex %USERPROFILE%\texmf\tex\latex\

```

6. Move all documentation files to the proper destination.

```
Windows Usage
C:\> move *.dvi %USERPROFILE%\texmf\tex\doc\

```

7. If the installation involves fonts then you also have to move the font-related files to their proper destination. Table 17.1 lists the destination directories for the font files. The name <vendor> is the name of the vendor/supplier of the font and is the name of the font. Some vendor directory names are standardised [Berry 1990] but any name is allowed.
8. At this stage it's safe to remove your temporary directory.
9. Complete the installation by updating the ls-R database in your local texmf directory.

```
Windows Usage
C:\> texhash %USERPROFILE%\texmf
```


CHAPTER 18

Using L^AT_EX on Unix

THIS CHAPTER EXPLAINS how to install a free and widely available L^AT_EX distribution called T_EX Live on Unix, how to use a widely used L^AT_EX IDE called TeXworks, and a B_IB_TE_X IDE called JabRef.

T_EX Live is easy to install and use. For example, this book was typeset with a standard T_EX Live installation without any special configurations. Another advantage of using T_EX Live is that it works on Windows, on Unix, and on the Mac. This is also one of the reasons for choosing the L^AT_EX and B_IB_TE_X IDEs. However, the IDEs were also chosen because they are easy to use.

The remainder of this chapter starts by explaining how to uninstall your previous T_EX Live installation and how to install T_EX Live. This is followed by some sections explaining how to use TeXworks and JabRef. The last section explains how to install class and package files.

18.1 Removing Your Previous Installation

If this is the first time you're installing T_EX Live, or if your current T_EX Live installation is from a previous year, you may proceed to the next section. Otherwise, you have to uninstall your previous version. You may need administrator permissions to remove the previous installation, so make sure you log in as root if you need them.

- If your T_EX Live was installed by your OS then you should remove it with your OS package manager. For example, on Ubuntu you could uninstall T_EX Live by running `apt-get remove texlive`.
- If your T_EX Live installation was installed using the T_EX Live installer, then you may remove the installation by running the command `tlmgr uninstall` from the command line.

```
# tlmgr uninstall
```

Unix Usage

18.2 Installing T_EX Live

This section explains how to install T_EX Live. If you have internet access, you can download a T_EX Live installer from <http://tug.org/texlive/acquire-netinstall.html>. If you don't have internet access or if internet access is slow, you can install T_EX Live from a *T_EX Collection* DVD. You may get a copy of the DVD from a friend, from a T_EX user

group, or (if you have it) from your local IT support. A list of all T_EX user groups may be found at <http://www.tug.org/usergroups.html>. Installing from DVD is similar to installing from the internet. To simplify the presentation, this section assumes you have internet access.

18.2.1 Downloading the Installer

The recommended method for installing T_EX Live is using the *network installer*, which downloads the T_EX Live distribution as part of the installation process. To download the network installer, go to <http://tug.org/texlive/acquire-netinstall.html>, click on the *install-tl-unx.tar.gz* link, and save the installer on your desktop.

18.2.2 Running the Installer

The main installation process is not much more difficult than downloading the installer. The following are the main details.

Throughout it is assumed that you have root access. We shall install T_EX Live in the directory `/usr/local/texlive`. Make sure you are logged in as root.

When you install T_EX Live as root you want to make sure all users have access to all files in the T_EX Live distribution. The easiest way to achieve this is by setting the `umask` to 022. This gives root read, write, and execute (search) permissions, and all other users read and execute (search) permissions. This step is crucial, don't forget it.

```
# umask 022 Unix Usage
```

Next you create the parent directory for the T_EX Live installation and make it the working directory.

```
# mkdir -p /usr/local/texlive Unix Usage
# cd /usr/local/texlive
```

The next step is uncompressing the installer that was saved on your desktop. As part of this step you may as well remove the file from your desktop.

```
# tar xfz ~/Desktop/install-tl-unx.tar.gz Unix Usage
# rm ~/Desktop/install-tl-unx.tar.gz
# ls
install-tl-⟨number⟩
```

The number at the end of the install directory is a combination of the year and the version. Proceed by making the install directory your working directory.

```
# cd install-tl-⟨number⟩ Unix Usage
# ls
LICENSE.CTAN  README.usergroups  readme-html.dir    tlpkg
LICENSE.TL   index.html         readme-txt.dir
README       install-tl         release-texlive.txt
```

The script `install-tl` is what you're after. Run it.

```
# ./install-tl Unix Usage
```

After a few seconds the script should show a text-based installation menu similar to the menu in Figure 18.1.

Usually, the default installation should work, which is why it's safe to start the installation process. You start the installation process by entering `I`(`return`). The installation process may take anything from a few minutes to an hour or so. The duration depends on the speed of your internet connection. Eventually, the installation should finish. When this happens, type `Q`(`return`) to quit the installer and *make sure* you log off as root.

18.2.3 Setting the Environment Variables

Finally, you must set some search path related variables. This should be done at the user level so make sure you log off as root.

The T_EX Live installer puts executables such as `latex`, `pdflatex`, and others in the executable directory `/usr/local/texlive/<year>/bin/i386-linux`, where `<year>` is the year of the distribution. T_EX Live is installed in `/usr/local/texlive` and the distribution is from 2011. Therefore, the executable directory is given by `/usr/local/texlive/2011/bin/i386-linux`. One of the configuration tasks is adding this directory to the `PATH` environment variable.

To ease the burden of setting the path related variables, we shall define an auxiliary variable that holds the path to the T_EX Live installation. You should define this variable in your `.login` file.

```
export TEXDIR=/usr/local/texlive/2011 Unix Usage
```

Next you change the `PATH` variable in your `.login` file. You do this by adding the following lines to your `.login` file. Note that this should be *after* the definition of the variable `TEXDIR`.

```
export PATH=${TEXDIR}/bin/i386-linux:${PATH} Unix Usage
```

You only have to add this line once. For subsequent T_EX Live installations, changing the value of the year in `TEXDIR` should suffice.

Next you modify the manual and info paths. This should also be done after the definition of `TEXDIR`. You should keep these lines for subsequent T_EX Live installations.

```
export MANPATH=${TEXDIR}/texmf/doc/man:${MANPATH} Unix Usage
export INFOPATH=${TEXDIR}/texmf/doc/info:${INFOPATH}
```

Except for some minor configuration, which is explained in the next section, you are now done with the installation process.

18.2.4 Minor Configuration

Usually, T_EX Live does a pretty good job when it comes to selecting the defaults. However, it may get things wrong when it comes to the

Figure 18.1
The TeX Live installation menu
on Unix

```
<B> platforms: 1 out of 19
<S> installation scheme (scheme-full)
      84 collections out of 85, disk space required: 2638 MB

Customizing installation scheme:
  <C> standard collections
  <L> language collections

<D> directories:
  TEXDIR (the main TeX directory):
    /usr/local/texlive/2011
  TEXMFLOCAL (directory for site-wide local files):
    /usr/local/texlive/texmf-local
  TEXMFSYSVAR (directory for variable and automatically generated data):
    /usr/local/texlive/2011/texmf-var
  TEXMFCONFIG (directory for local config):
    /usr/local/texlive/2011/texmf-config
  TEXMFVAR (personal directory for variable and automatically generated data):
    ~/.texlive2011/texmf-var
  TEXMFCONFIG (personal directory for local config):
    ~/.texlive2011/texmf-config
  TEXMFHOME (directory for user-specific files):
    ~/texmf

<O> options:
  [ ] use letter size instead of A4 by default
  [X] allow execution of restricted list of programs via \writel8
  [X] create all format files
  [X] install macro/font doc tree
  [X] install macro/font source tree

<V> set up for portable installation

Actions:
  <I> start installation to hard disk
  <H> help
  <Q> quit

Enter command:
```

default paper size, which is set to A4. If you require an 8.5 × 11 inches paper size, the easiest way to make this the default paper size is running the command `tlmgr paper letter` from the command line. There is also a GUI for `tlmgr` but it is not explained to simplify the presentation.

```
user@machine:~$ tlmgr paper letter
```

Unix Usage

18.2.5 Testing the Installation

At this stage it is a good idea to test the installation. Note that this requires logging off and on. If you don't log off and on then your OS will not know the new values of the environment variables. To test your installation you could create a L^AT_EX input file and process it with `pdflatex`. However, it may be easier to compile one of the files that come with T_EX Live. For example, you should be able to compile the file `small2e.tex` by executing the command `pdflatex small2e.tex` from the command line.

```
user@machine:~$ pdflatex small2e.tex
```

Unix Usage

Thanks to the T_EX Live Team, the test passes with flying colours.

18.3 First Steps with TeXworks

TeXworks is a L^AT_EX IDE that is based on an award-winning L^AT_EX Mac IDE called TeXShop. TeXworks has a simple user interface and is freely available. TeXworks also works on Windows and on the Mac (as TeXShop). These are the main reasons why TeXworks is the only L^AT_EX IDE that is explained in this chapter.

To install TeXworks, visit http://www.tug.org/texworks/#Getting_TeXworks and follow the installation instructions.

This section explains how to create and compile the L^AT_EX input in Figure 18.2. The L^AT_EX input file depends on a tiny bibliography file called `LAF.bib`, which is listed in Figure 18.3. To save time, you may download both files from <http://cswb.ucc.ie/~dongen/LAF/Extras/bibliographies.tex> and <http://cswb.ucc.ie/~dongen/LAF/Extras/LAF.bib>.

Start by running TeXworks and by loading the input program. The following explores the most important aspects of the TeXworks GUI.

- The TeXworks GUI is shown in the picture on the left of Figure 18.4.
- The green circle with the grey triangle in it is the *typesetting button*.
- To the right of the typesetting button is a drop-down list, which is called the *typesetting engine list*. You use it to select the current *typesetting engine*, which “typesets” your document.
- The typesetting engine is run when you click the typesetting button. The drop-down list always shows the current typesetting engine. In the picture on the left of Figure 18.4 the typesetting engine is pdfTeX.
- There are different typesetting engines: pdfLaTeX, BibTeX, MakeIndex,

Figure 18.2
 \LaTeX input for bibliography example

```

\documentclass[11pt]{book}
\usepackage[style=authoryear,
            block=space,
            language=british]{biblatex}
\renewcommand*{\bibopenparen}{[}
\renewcommand*{\bibcloseparen}{]}
\renewcommand*{\bibnamedash}{\rule[0.48ex]{3em}{0.14ex}\space}
\addbibresource{LAF}

\begin{document}
  \chapter{Philip Glass}
  \begin{refsection}
    Philip Glass' \emph{Analog}~\parencite{Analog} \ldots
  \end{refsection}
  \chapter{Steve Reich}
  \begin{refsection}
    Steve Reich's \emph{Come Out}~\parencite{Come@Out} \ldots
    \emph{Music for 18~Musicians}~\parencite{18@musns} \ldots
  \end{refsection}
  \printbibliography[section=1,title=Philip Glass Discography]
  \printbibliography[section=2,title=Steve Reich Discography]
\end{document}

```

Figure 18.3
 \BibTeX input for bibliography example


```

@Misc{Analog,
  author = {Glass, Philip},
  title  = {Analog},
  year   = {2006} }
@Misc{18@musns,
  author = {Reich, Steve},
  title  = {Music for 18~Musicians},
  year   = {1976} }
@Misc{Come@Out,
  author = {Reich, Steve},
  title  = {Come Out},
  year   = {1966} }

```

pdfTeX, For example, when pdfLaTeX is the typesetting engine, pdfL_AT_EX is used to typeset the document, when BibTeX is the typesetting engine, bib_TE_X is used to “typeset” the document, and so on. Note that typesetting engines are defined at the TeXworks level: they drive executable programs. For example, the pdfLaTeX engine drives the pdfL_AT_EX executable.

- You may change the current typesetting engine by selecting it from the typesetting engine list. This is shown in the picture on the right of Figure 18.4, which selects pdfL_AT_EX.


Figure 18.4

Setting the typesetting engine. The picture on the left shows TeXworks with pdfTeX as the current typesetting engine. The picture on the right shows how the typesetting engine is changed to pdfLaTeX by selecting it from the drop-down list to the right of the typesetting button.

You now know the basics of the TeXworks GUI. You might as well start using it:

1. This book uses a pdf_latex philosophy, so make sure you pdf_Latex is selected in the typesetting engine list.
2. Proceed by typesetting the document, which you may do by clicking the typesetting button.
3. When you click the button, this should create your output document and should pop up a pdf viewer that displays the output document. Here it is assumed you downloaded the input program and didn't change it. If you have errors, then you may have to resolve the errors and typeset the document until all errors are gone.

Congratulations. You have just overcome the first obstacle on the short path of becoming a TeXworks expert.

On closer inspection the output document isn't perfect. For example, the citation commands in the text only list the logical citation labels, and there is no bibliography. The following section explains how to resolve these problems.

18.4 Creating Bibliographies with TeXworks


This section explains how to create proper bibliographies in combination with TeXworks. We shall continue with the example from the previous section. Make sure you have saved the B_IB_TE_X input from Figure 18.3 in a file called LAF.bib. It is recommended you download the B_IB_TE_X input from <http://csweb.ucc.ie/~dongen/LAF/Extras/LAF.bib>.

18.4.1 Creating One Single Bibliography

As explained in the first chapter, running pdf_latex alone cannot guarantee a consistent bibliography. If you want to create your bibliography with B_IB_TE_X, you also have to run bib_tex. In this section you learn

Figure 18.5

Configuring TeXworks for multiple bibliographies. The TeXworks Preference menu on the left pops up when you click edit→preferences and then select the Typesetting tab. Selecting BibTeX and clicking Edit pops up the menu on the right. This is where you configure the BibTeX engine. The Program text field determines the program that is executed for the BibTeX engine, and the Arguments text field determines its argument.



how to create a bibliography with TeXworks. For simplicity, we shall continue the example from the previous section. Start TeXworks, load the example, and typeset it once with the pdfLaTeX engine.

Most documents have only one bibliography. Remember from Chapter 1 that you compile such documents, by first running pdf`latex`, then running `bibtex`, and then running pdf`latex` two more times. You already know how to run pdf`latex` from within TeXworks. If only you could execute `bibtex` from within TeXworks Fortunately, this is possible. You can run `bibtex` by typesetting your document with the BibTeX engine. You see why TeXworks is easy?

1. Start by making BibTeX your typesetting engine.
2. Execute `bibtex` by clicking the typesetting button.
3. Continue by making pdfLaTeX your typesetting engine again.
4. Complete the process by typesetting your document two more times. You do this by clicking the typesetting button twice.

For documents with one bibliography, the previous procedure is enough to get perfect bibliographies. Unfortunately, our L^AT_EX input file has more than one bibliography. When you typeset such documents with the BibTeX engine, TeXworks only runs `bibtex` on one auxiliary bibliography file. In the next section we shall configure TeXworks so it will run `bibtex` on all auxiliary bibliography files.

18.4.2 Creating Several Bibliographies

As explained in the previous section the BibTeX typesetting engine only runs `bibtex` on one auxiliary bibliography file. In this section we shall configure the engine so that `bibtex` is executed for each relevant file. After the configuration the BibTeX typesetting engine should work correctly for any number of bibliographies.

To configure the BibTeX typesetting engine, you do the following.

1. Select Edit→Preferences. This pops up the Preference menu.
2. Proceed by selecting the Typesetting tab. This activates the Typesetting Menu. This is shown on the left of Figure 18.5.
3. In the Processing Tools list select BibTeX. This pops up the Tool Configuration menu for the BibTeX typesetting engine. This is shown on the right of Figure 18.5.
4. The Program text box in the Tool Configuration menu determines the program that TeXworks executes when you typeset your document with the BibTeX engine. Enter `bibtex-all`; we shall implement this user-defined script later.
5. The Arguments text box in the Tool Configuration menu determines which arguments are passed to our user-defined script. Enter `$basename`.
6. Accept the current configuration by repeatedly clicking the Ok buttons until the Preference menu is gone.
7. At this stage, you're almost done. All that's left is implementing the user-defined script, which should have the following commands. You may download the script from <http://csweb.ucc.ie/~dongen/LAF/Extras/unix/bibtex-all>.

```
#!/bin/sh
for FILE in $@*.aux; do
    bibtex ${FILE}
done
```

Unix Usage

8. Save the script as `bibtex-all` in a directory that is in your PATH, and make sure the script is executable.

You should now be able to create your bibliographies by typesetting your document once with the BibTeX typesetting engine and twice with the pdfLaTeX typesetting engine.

18.5 Creating Indexes with TeXworks

In this section we shall create an output document with indexes. We shall do this using the L^AT_EX input that is depicted in Figure 18.6. You may download the input from <http://csweb.ucc.ie/~dongen/LAF/Extras/indexes.tex>.

Creating the indexes is done by typesetting the document with the MakeIndex engine. Unfortunately, this will only create one proper index, so you have to configure the MakeIndex engine. You may do this with a similar technique as the technique for configuring the BibTeX typesetting engine. The following explains the configuration process.

1. Select Edit→Preferences. This activates the Preference menu.
2. Proceed by selecting the Typesetting tab.
3. In the Processing Tools list select MakeIndex and click the Edit button. This should activate the Tool Configuration menu for the MakeIndex typesetting engine.
4. Enter `makindex-all` in the Program text box; we shall implement this user-defined script later.

Figure 18.6
 \LaTeX input for indexes example

```

\documentclass[llpt]{article}
\usepackage{multind}

\makeindex{programs}
\makeindex{authors}
\begin{document}
  Knuth\index{authors}{Knuth} is the author of
  \TeX\index{programs}{TeX@\TeX}.

  \printindex{programs}{Index of Programs}
  \printindex{authors}{Index of Authors}
\end{document}

```

5. There is no need to enter anything in the Arguments text box. The reason for this is that the names of the index files don't depend on the \LaTeX document name, so `makeindex` has to process all `.idx` files.
6. Accept the current configuration by repeatedly clicking the `Ok` buttons until the Preference menu is gone.
7. Implementing the user-defined script completes the configuration. The following is the script. You may download the script from <http://cswb.ucc.ie/~dongen/LAF/Extras/unix/makeindex-all>.

```

#!/bin/sh
for FILE in *.idx; do
  makeindex ${FILE}
done

```

8. Save the script as `makeindex-all` in the same directory as `bibtex-all`. Make sure the script is executable.

You should now be able to create your indexes by (1) typesetting your document with the pdf \LaTeX typesetting engine, (2) typesetting it with the MakeIndex typesetting engine, and (3) typesetting it two more times with the pdf \LaTeX typesetting engine.

18.6 The LaTeXmk Typesetting Engine

The previous two sections explained how to configure TeXworks for multiple bibliographies and multiple indexes and how to compile your document in a “traditional” manner. A fairly recent development is compiling your documents with *latexmk*, which is equivalent to a make script for \LaTeX .

At the time of writing this chapter, *latexmk* was sufficiently advanced that it could typeset most documents automatically. You just run `latexmk -pdf` on your \LaTeX source file, and the software will execute `pdflatex`, `bibtex`, and `makeindex` on all relevant files until it reaches a fixpoint (until there are no more changes). Needless to say, using *latexmk* is much easier than running several different programs by hand. The only disadvantage of the *latexmk* approach is that *latexmk*

may take a bit longer. Further information about `latexmk` may be found on <http://www.phys.psu.edu/~collins/software/latexmk-jcc/>.

TeXworks also has a LaTeXmk typesetting engine. As suggested by the name, the engine compiles your input document with `latexmk`. If you are the kind of person that wants to do things the easy way, then this may be the typesetting engine for you.

18.7 Bibliography Management with JabRef

JabRef [*JabRef*] is an open source BIB_TE_X IDE. JabRef requires JVM version 1.5 or newer and should run on any machine that has a JVM running. If you don't have a JVM on your machine, visit the JabRef FAQ at <http://jabref.sourceforge.net/faq.php> for instructions on how to best install it.

JabRef has an advanced BIB_TE_X editor, a search engine that lets you search for patterns in the bibliography, an import facility for various other bibliography formats, automatic key generation, and a search facility that lets you search Search Medline, Citeseer, IEEEExplore and arXiv on line.

The remainder of this section is a very short introduction to JabRef, which should be just enough to create a new BIB_TE_X file and edit it. This should be enough to get started; you may learn more about JabRef from its built-in help function.

18.7.1 Installing JabRef

Installing JabRef is easy. To install JabRef, visit the JabRef download page at <http://jabref.sourceforge.net/download.php> and click one of the download buttons for the latest stable version. Click on the link `JabRef-⟨number⟩.jar` and save it in a suitable place. From now on you may start JabRef by executing the command `java -jar ⟨jar file⟩`, where `⟨jar file⟩` is the path leading to the file `JabRef-⟨number⟩.jar` that you've just saved.

18.7.2 Using JabRef

This section explains how to create and modify a BIB_TE_X file with JabRef. It uses the tiny BIB_TE_X file that is depicted in Figure 18.7. You may download the file from <http://csweb.ucc.ie/~dongen/LAF/Extras/JabRef.bib> and save it as `JabRef.bib`.

Start JabRef and open the bibliography database `JabRef.bib`. You should now see the picture at the top of Figure 18.8. The IDE is rather intuitive and shows the different kinds of entries in the BIB_TE_X file: there are two books and one article. The globe on the left side of the entry for the `TeXbook` corresponds to the `url` field in the BIB_TE_X file. Clicking on the globe leads to the `URL` in the `url` field. The BIB_TE_X keys are listed in the column `Bibtexkey`. If this column is bit too far to the right to your liking, then you can drag it to a different position. This

Figure 18.7
Sample JabRef bibliography
input

```

@Book{Knuth:1990,
  title      = {The {\TeX}book},
  publisher  = {Addison\textendash Wesley},
  year       = {1990},
  author     = {Knuth, Donald E.},
  isbn       = {0-201-13447-0},
  url        = {http://www.ctan.org/tex-archive/systems/knuth/tex/}
}
@Article{Knuth:78,
  author     = {Knuth, Donald E.},
  title      = {The Average Time for Carry Propagation},
  journal    = {Indagationes Mathematicae},
  year       = {1978},
  volume     = {40},
  pages      = {238-242}
}
@Book{Lamport:94,
  title      = {{{\LaTeX}: \emph{A Document Preparation System}}},
  publisher  = {Addison\textendash Wesley},
  year       = {1994},
  author     = {Lamport, Leslie},
  isbn       = {0-021-52983-1}
}

```

is shown in the picture at the bottom of Figure 18.8. Other columns may be repositioned similarly.

To create a new entry for an article, select BibTeX→New entry, and select Article as the entry type. Clicking the green plus icon is an alternative selecting BibTeX→New entry. In the menu that pops up, enter the fields for some real or fictional article. The picture at the top of Figure 18.9 shows the result of filling out the fields required fields Author, Title, Journal, Year, Volume, and Pages. You may fill in the Bibtexkey field with an explicit key. If you're stuck for a choice, JabRef will generate a key for you if you click the magic wand icon, which is to the left of the Title text field.

If your article is in a journal that has a number, you have to fill out the optional Number entry. You may do this by clicking the Optional fields tab and entering the number in the Number text field. The picture at the bottom of Figure 18.9 shows the result. You may save the current BIBTEX database, including the new article entry, by selecting File→Save database or by clicking the (single) floppy disk icon.

18.8 Installing Classes and Packages

This section explains the two basic class and package installation techniques in T_EX Live. The first and preferred technique uses the tlmgr program, which is provided by T_EX Live. The second technique is “installing by hand,” which is prone to errors.




Figure 18.8

JabRef IDE. The picture on the top shows the original IDE. In the picture on the bottom, the Bibtexkey column is dragged to just before the Owner column.





Figure 18.9

Creating a new B_IB_TE_X entry. The figure at the top shows the Required fields tab with filled out text fields for the required entries of an article. The figure on the bottom shows the Optional fields tab with the filled out text field for the number of the journal.



Installing class and package files is impossible unless you know a little bit about how T_EX Live organises its files, and how T_EX Live executables locate these files. The first three sections provide a quick introduction to the required background. The last two sections explain how to install class and package files. Throughout, the word package is a synonym for class or package.

18.8.1 The T_EX Directory Structure

T_EX Live distributions are huge and with the current technology of operating systems it is impossible to quickly locate a file that is located underneath some directory. What is more, T_EX Live distributions cannot guarantee unique file names. For example, an auxiliary file called `aux.tex` may occur in more than one directory.

The TUG Working Group on a T_EX Directory Structure TWG-TDS [2004] defined a TDS, which is specifically designed to overcome problems related to the efficient location of files in a T_EX distribution. T_EX Live has adopted the TDS and many classes and packages assume an underlying TDS.

Note that a TDS is a property of a directory and several directories may have a TDS. For example, if you accept all defaults when you install T_EX Live on Unix, then the global T_EX Live files are in the directory `/usr/local/texlive/<year>`, where `<year>` is the year of the T_EX Live distribution. At the directory's root is a large directory called `texmf-dist`, which has a TDS. Effectively, this is where T_EX Live keeps most of its class and package files. Likewise, T_EX Live assumes the existence of a user directory called `~/texmf`, which should also have a TDS.

Within a TDS-compliant directory, each type of file is expected in a specific place. Figure 18.10 depicts some of the aforementioned TDS `texmf-dist`. At the root level the figure shows the directories `bibtex`, `doc`, `fonts`, and `tex`. As suggested by the names, the directory `bibtex` is for B_IB_TE_X related files, `doc` is for documentation, `fonts` is for font files, and `tex` is for T_EX files. L_AT_EX files should be put in the directory `lstex/latex`, which should have a subdirectory for each package. The figure shows two such package directories: `siunitx` and `url`. The main purpose of each package directory is storing “its” package files.

18.8.2 Updating an `ls-R` Database

When a T_EX Live executable such as `pdflatex` has to locate a package, it uses a library called `kpathsea` [Berry, Weber, and Hoekwater 2011], which uses several different techniques to locate the package. One of these techniques is looking up the package location in a plain-text `ls-R database`, of which there may be several.

The name of an `ls-R` database is always the same: `ls-R`. Because the name of each `ls-R` database is unique, there can be no more than one `ls-R` database in a given directory. We say that an `ls-R` database is *rooted* in the directory that it is in. Likewise, we say that a directory is




Figure 18.10

TeX directory structure (TDS). The directory `texmf-dist` at the root of the depicted directory tree is where TeX Live keeps its files. The directories inside `texmf-dist`, form a hierarchical structure that is common to other TDS-compliant directories. At the top level the directories `bibtex`, `doc`, `fonts`, and `tex` have a prescribed structure. For example, the directory `texmf-dist/tex/latex` has one directory for each standard installed package. The package files are then organised inside their directory. For example, the `url` package file is located in the file `tex/latex/url/url.sty` inside `texmf-dist`. The files for the `siunitx` package are located in the subdirectory `tex/latex/siunitx/siunitx.sty`.

the *root* of its `ls-R` database. The main purpose of an `ls-R` database is to store the locations of classes, packages, and other files in the database’s root directory and descendant directories.

Remember that you may install a package with `t1mgr` or by hand. When `t1mgr` installs a package, `t1mgr` updates all the relevant `ls-R` databases. When a package is installed in one of these `ls-R` directories (or one of its descendant directories), this usually requires updating the `ls-R` database. You may do this by executing the following command.

```
# texhash <root directory> Unix Usage
```

Here `<root directory>` is the root directory of the `ls-R` database. If `root directory` is large, running the command may take a while. Note that you need write access to the database, so you may need administrator access to do this.

18.8.3 How `kpathsea` Finds its Files

As explained earlier on in this chapter, \TeX Live executables delegate the task of locating classes, packages, and other files to the `kpathsea` library [Berry, Weber, and Hoekwater 2011]. This section explains this process in more detail. To simplify the presentation, this section only discusses how `kpathsea` locates package files. The process for \LaTeX (`.tex`), class (`.cls`), and other types of files is similar [Berry, Weber, and Hoekwater 2011].

When `pdflatex` formally asks `kpathsea` for the location of a given package called `<package>`, the library starts by constructing a *search path*. Berry, Weber, and Hoekwater [2011, section 3.2] explains how the search path is constructed.

A `kpathsea` search path is a list of colon-separated *path elements*. Each path element consists of a single annotated directory. The annotation determines how the directory should be searched for `<package>`.

As expected, `kpathsea` processes the path elements in the search path from left to right until it finds the location of `<package>` or fails.

1. When `kpathsea` processes the next path element, it starts by extracting the directory, `<directory>`, from the path element.
2. If one of the prefixes of `<directory>` is the root of an `ls-R` database, then `kpathsea` tries to look up the location of `<package>` in that `ls-R` database [Berry, Weber, and Hoekwater 2011, page 27]. If this operation succeeds, then `kpathsea` returns the resulting location. (Berry, Weber, and Hoekwater [2011] implies that there should be no more than one `ls-R` database along any path leading from any directory to any leaf directory. Furthermore, the name of the `ls-R` database should be in the internal `kpathsea` variable `TEXMFDBS`. This was confirmed by Karl Berry in private communication.)
3. Otherwise, `kpathsea` considers the annotation of the path element.
4. If the path element is of the form `!!<directory>`, `kpathsea` stops processing the path element.
5. If the path element is of the form `<directory>//`, `kpathsea` completes processing the path element by searching `<directory>` recursively for `<package>`.
6. If the path element is of the form `<directory>`, `kpathsea` completes processing the path element by searching `<directory>` without recursion. It is assumed the directory has a `TDS`.
7. (Other path element forms are not allowed.)

The following command outputs the `kathsea` search path for `pdflatex` and style files.

```
# kpsewhich -programe pdflatex -show-path .sty Unix Usage
```

When you run this, many of the path elements in the output have directories that are annotated with the `!!` prefix. If you install a new package in one of these directories (or descendant directories thereof)

then the `ls-R` database in that directory *must* be updated. If you forget updating the database, the package may never be found.

18.8.4 *Installing Packages with tlmgr*

As already mentioned, the `tlmgr` program is provided as part of T_EX Live. The main purpose of `tlmgr` is updating and installing packages and classes that are part of T_EX Live. The program can also update itself. You don't need administrator access to use the program.

If you want to install a class or package that is part of T_EX Live then installing them with `tlmgr` is by far the easiest. Not only will `tlmgr` install the class or package for you but it will also update any relevant `ls-R` database. The following is how you install classes and packages with `tlmgr` from the command line. There is also a `tlmgr` GUI but this is not explained here.

tlmgr install `<names>`

This installs the classes and packages in the list `<names>`. There is no need to add extensions in `<names>`.

There is also a `tlmgr` GUI but this is not explained here.

The following are some other useful `kpathsea` options for day-to-day use.

tlmgr -help

This provides a short explanation of how to use `tlmgr`. For complete information, visit <http://tug.org/texlive/doc/tlmgr.html>.

tlmgr update `<names>`

This updates the classes and packages in the list `<names>`. There is no need to add extensions in `<names>`.

tlmgr update --all

This updates all classes and packages.

tlmgr update --self

This updates `tlmgr` itself. This option may be required if your T_EX Live distribution is too old.

tlmgr update --self --all

This updates `tlmgr` and all classes and packages.

The `tlmgr` program can also make backups, restore backups, and lots of other things. The package documentation at <http://tug.org/texlive/doc/tlmgr.html> provides further information.

18.8.5 *Installing Packages by Hand*

The previous section showed that installing packages with `tlmgr` is easy. Unfortunately, not all packages are supported by T_EX Live, some have to be installed by hand.

Installing classes and packages by hand requires a bit more work than installing with `tlmgr`. Fortunately, it is not much more difficult if you install them in your *local texmf tree*—a TDS that is reserved for user-defined class and package files [Berry 2011, page 11].

You may get the location of your (local) `texmf` tree by executing

the command `kpsewhich var-value=TEXMFHOME` from the command line. By default \TeX Live uses `~/texmf` for your `texmf` tree.

Remember from the second last section that the command `kpsewhich -programe pdflatex -show-path .sty` shows the search path for package files. If \TeX Live is installed with all the defaults, this command should list your local `texmf` tree in a path element that is suffixed with `//` annotation. Recall that the `//` suffix means that `kpathsea` searches the directory recursively. If all you have to do is installing a single file then creating a subdirectory for the package in your local `texmf` tree and putting the file in that directory should be enough. If the package you're installing is based on a `TDS` then unpacking the files in the root of your local `texmf` tree should suffice. After this you may, but this is not required update the `ls-R` database at the root of your local `texmf` tree. (Remember that you may do this with the command `texhash`.)

Unfortunately, not all packages are provided as a `TDS` and you may have to uncompress the files, build the package documentation, move all files to their destination directories, and update the `ls-R` database. The following shows how to do this for a package called `<package>`.

1. Create a temporary directory. Download, save, and if necessary extract the package files in this temporary directory.
2. Usually there is a `.ins` file. If there is, run `pdflatex` on it.
3. If there is a `.dtx` file then you must create the class or package documentation. You do this by running `pdflatex` once or twice on the `.dtx` file.
4. What remains is moving the files to the correct location in the local `texmf` tree. In the following it is assumed the local `texmf` tree is in the default \TeX Live location: `~/texmf`. Start by creating the destination directories for the \LaTeX files and for the documentation.

```
# mkdir -p ~/texmf/tex/doc/<package>
# mkdir -p ~/texmf/tex/latex/<package>
```

Unix Usage

5. Move all \LaTeX files to the proper destination.

```
# mv *.tex *.sty *.cls *.fd ~/texmf/tex/latex/<package>
```

Unix Usage

6. Move all documentation files to the proper destination.

```
# mv *.dvi *.pdf *.ps ~/texmf/tex/doc/<package>
```

Unix Usage

7. If the installation involves fonts then you also have to move the font-related files to their proper destination. Table 18.1 lists the destination directories for the font files. The name `<vendor>` is the name of the vendor/supplier of the font and `` is the name of the font. Some vendor directory names are standardised [Berry 1990] but any name is allowed.
8. At this stage it's safe to remove your temporary directory.
9. Complete the installation by updating the `ls-R` database in your local `texmf` directory.

Extension	Destination in ~/texmf/fonts
.afm	afm/<vendor>/
.map	map/pdftex/<vendor>
.pfb	type1/<vendor>/
.tfm	tfm/<vendor>/
.ttf	truetype/<vendor>/
.vf	vf/<vendor>/

Table 18.1

TeX Live font directories. The first column lists the extension of the font files. The second column lists the destination directory for these files. The destination is relative to ~/texmf/fonts.

```
# texhash ~/texmf
```

Unix Usage

PART VII

**References
and
Bibliography**

Picture omitted to keep size of .pdf small.

Oil and charcoal on canvas (08/10/10), 64 × 91 cm
Work included courtesy of Billy Foley
© Billy Foley (www.billyfoley.com)

Typographic Jargon

THIS IS A SHORT REFERENCE of typographic jargon. The presentation is not top-down but lists the jargon in alphabetical order. More detailed information may be found in good typography books such as, for example, [Felici 2012].

baseline The baseline is the virtual reference line that the characters are written on. Parts of some of the letters may stick out below the baseline. For example, letters like *g*, *j*, and *p* stick out below the baseline. Figure 18.11 provides an example.

bounding box The bounding box of a character is the virtual rectangle containing the character. Each box has a reference point, a height, a width, and a depth. See Figure 18.12 for an example. The boxes are designed to combine their characters on the baseline by chaining their boxes. This explains why some characters are not contained entirely by their bounding boxes. Figure 18.13 shows how the boxes from Figure 18.12 are combined.

character A character is a member of a typeface.

em The relative length unit em is a synonym for the current type size.

em space An em space is a horizontal space with a length of 1 em.

en An en is a relative length unit that is equal to half an em.

font A computer font is the software that defines a typeface.

font family A font family is a collection of fonts that define a typeface family.


glyph A glyph is a certain form of a character. Different characters usually have different glyphs but the converse is not true. For example, the letter *a* has several different glyphs: *a*, and so on.

italic typeface An italic typeface is a slanted typeface that is usually based on calligraphic handwriting.


kerning Kerning refers to adjusting the space between adjacent glyph pairs that are too close or too far apart. Kerning is needed because the bounding box of a glyph may not always be compatible with the bounding box of any other glyph. When this happens kerning adjusts the position of the glyphs by moving the relative position of their bounding boxes. Figure 18.15 shows how kerning works. In this example kerning reduces the distance of the glyph pairs but kerning may also increase the distance. Kerning may also move glyphs up or down.

Figure 18.11


Baseline and mean line. The solid line is the baseline, which the letters/glyphs are written on. The dashed line is the mean line. The mean line limits the height of the nonascending lowercase letters. Uppercase letters and letters such as *f*, *h*, and *k* stick out above the mean line. Letters such as *g* and *p* stick out below the baseline. The distance between baseline and mean line is the x-height.

**Figure 18.12**


Bounding boxes. Each letter is contained in its bounding box, which is drawn with a dashed line. Words are created by sequencing letter boxes (see Figure 18.13). Letters may extend beyond the box outline if this makes it easier to sequence the boxes. The circle on the baseline is the box's reference point. Each box has a height, a width, and a depth. The height (depth) measures the part above (below) the baseline.

**Figure 18.13**

Word formation. The word 'if' is formed by sequencing the bounding boxes of the letters *i* and *f*. The right side of the bounding box of the *i* touches the left side of the bounding box of the *f* and the reference point of the bounding boxes are on the same horizontal line.

**Figure 18.14**

Computing the point size. The point size is determined by the sum of the largest possible height and the largest possible depth of the letters in the font at the current size.






Figure 18.15

Kerning. The distance between the letters in the pairs ‘Ve’ and ‘Ti’ on the first line is too large. In the second line this is resolved by adjusting the distances within the pairs. This is called kerning. In this example, kerning reduces the distance between the reference points of the bounding boxes, which makes the bounding boxes overlap. The overlap is shown in grey.




Figure 18.16

Ligatures. This figure shows two examples of ligatures. At the top are the ligatures and at the bottom the letters that form the ligatures.

leading The leading or line spacing is the distance between the baselines of two subsequent lines in the text.

letterspacing Letterspacing or tracking refers to the uniform amount of space that is added to the left and right of the characters in a passage of text.

ligature A ligature is a glyph that represents a combination of two or more individual letters, digits, or punctuation marks. Figure 18.16 shows two examples of ligatures.


line spacing See leading.

mean line The mean line is the virtual demarcation line for the height of the lowercase letters without ascenders. See Figure 18.11 for an example.

oblique typeface See slanted typeface.

Figure 18.17

Seriffed versus sans serif letters. The letters on the left have serifs, which are drawn in black. The rest of the letters is drawn in grey. The letters on the right lack serifs.



roman typeface A roman or upright typeface is a typeface whose glyphs have an upright shape. Usually the main text of papers and books is typeset in a roman typeface.

slanted typeface A slanted or oblique typeface is a typeface whose glyphs are slanted to the right. The resulting glyphs may be obtained by mathematically transforming the roman glyphs. However, some typefaces have a different design.

point A TeX point is an absolute length unit that is equivalent to $\frac{1}{72.27}$ inch. The point unit is denoted pt, so 72.27 pt is equal to 1 inch.

point size The point size or type size is a relative length unit. The point size depends on the font and current size. You get the point size of the font (at the given size) by taking the letters of the font and adding the largest height and the largest depth of the bounding boxes of the letters. Figure 18.14 illustrates the definition.

pt See point.

quad A L^AT_EX quad is a relative horizontal length unit that is equivalent to 1 em [Knuth 1990, page 314].

sans serif typeface A sans serif typeface is a typeface whose glyphs lack serifs. See Figure 18.17 for an example.

small caps Small caps letters have a similar shape as uppercase letters but they aren't as high so they blend in better with lowercase letters: abcd...xyx ABCD...XYZ.

serif A serif is a small decoration at the end of the strokes of some of the glyphs. See Figure 18.17 for an example.

seriffed typeface A seriffed typeface is a typeface (some of) whose characters have serifs.

thin space A thin space is usually set to $\frac{1}{4}$ em or about half the word space [Felici 2012]. In L^AT_EX a thin space is normally $\frac{1}{6}$ em [Knuth 1990, page 167].

tracking See letterspacing.

type The word type literally means form and refers to the metal blocks that were used for printing. Nowadays it refers to printable characters.

typeface A typeface is a collection of letters, digits, punctuation symbols, and other characters that share a common design and common features.

typeface family A typeface family is a collection of typefaces that share some features. Many typeface families come with a roman shape, an italic shape, a slanted shape, and so on. Examples of typeface families are *Computer Modern Roman*, *Computer Modern Sans Serif*, *Gentium*, *Linux Libertine Serif/Times New Roman*, \TeX *Gyre Heros/Helvetica*, \TeX *Gyre Pagella/Palatino Linotype*, and so on.

type size See point size.

typewriter typeface A typewriter or monospaced typeface is a typeface whose glyphs have equal width.

x-height The x-height is the distance between the mean line and the baseline. By design the distance coincides with the height of the lowercase *x*. See Figure 18.11 for an example.

Bibliography

- Abrahams, P. A., K. A. Hargreaves, and K. Berry [2003]. *T_EX for the Impatient*. Addison–Wesley. URL: <ftp://tug.org/tex/impatient>.
- Allen, Robert [2001]. *Punctuation*. Oxford University Press. ISBN: 0-19-860439-4.
- American Mathematical Society [5th Feb. 2002]. *User’s Guide for the *amsmath* Package*. Version 2.0.
- [5th Feb. 2002]. *Using the *amsthm* Package*. Version 2.20.
- Arnold, Doug [25th Jan. 2010]. *The L^AT_EX for Linguists Home Page*. URL: <http://www.essex.ac.uk/linguistics/external/clmt/latex4ling/>.
- Arseneau, Donald [20th Jan. 2010]. *url.sty*. Version 3.3. Edited as a L^AT_EX document by Robin Fairbairns.
- Aslaksen, Helmer [1993]. “Ten T_EX Tricks for the Mathematician”. In: *TUGboat* 14. A modern version of this paper is available from <http://www.math.nus.edu.sg/aslaksen/cs/tug-update.pdf>, 135–136.
- Bazargan, Kaveh, and C. V. Radhakrishnan [2007]. “Removing vertical stretch—mimicking traditional typesetting with T_EX”. In: *TUGboat* 28.1, 133–136. URL: <http://www.tug.org/TUGboat/tb28-1/tb88bazargan.pdf>.
- Beccari, Claudio [1997]. “Typesetting Mathematics for Science and Technology According to ISO 31/XI”. In: *TUGboat* 18.1, 39–48. URL: <http://www.tug.org/TUGboat/tb18-1/tb54becc.pdf>.
- Becker, T., and V. Weispfenning [1993]. *Gröbner Bases A Computational Approach to Commutative Algebra*. Graduate Texts in Mathematics. Springer. ISBN: 3-540-97971-9.
- Berry, Karl [1990]. “Filenames for Fonts”. In: *TUGboat* 11.4.
- ed. [1st June 2011]. *The T_EX Live Guide* T_EX Live 2011. URL: <http://tug.org/texlive>.
- Berry, Karl, Olaf Weber, and Taco Hoekwater [1st Apr. 2011]. *Kpathsea Library*. Version 6.0.1. URL: <http://tug.org/.kpathsea>.
- Bigwood, Sally, and Melissa Spore [2003]. *Presenting Numbers, Tables, and Charts*. Oxford University Press. ISBN: 0-19-860722-9.
- Borowski, Ephraim J., and Jonathan M. Borwein [2005]. *Collins Dictionary of Mathematics*. Collins. ISBN: 0-00-780080-0.
- Bovani, Michel [30th Jan. 2005]. *Fourier GUTenberg*.

- Breitenbucher, Jon [2005]. “L^AT_EX at a Liberal Arts College”. In: *PracT_EX Journal* 3. URL: <http://tug.org/pracjourn/2005-3/breitenbucher>.
- Bringhurst, Robert [2008]. *The Elements of Typographic Style*. Hartley & Marks. ISBN: 0-988179-206-3.
- Buchsbaum, Arthur, and Francisco Reinaldo [2007]. “A Tool for Logicians”. In: *The PracT_EX Journal* 3. URL: <http://tug.org/pracjourn/2007-3/buchsbaum>.
- Burt, John [2005]. “Using poemscol for Critical Editions of Poetry”. In: *PracT_EX Journal* 3. URL: <http://tug.org/pracjourn/2005-3/burt>.
- Carlisle, David [5th Mar. 1999a]. *The enumerate Package*. Version 3.00.
- [16th Mar. 1999b]. *The keyval Package*. Version 1.13.
- [28th May 2001]. *The dcolumn Package*. Version 1.06.
- Carlisle, D. P. [14th Nov. 2005]. *Packages in the graphics Bundle*.
- Carlisle, D. P., and S. P. Q. Rahtz [16th Feb. 1999]. *The graphicx Package*. Version 1.0f.
- Clapham, Christopher, and James Nicholson [2005]. *Oxford Concise Dictionary of Mathematics*. Third Edition. Oxford University Press. ISBN: 978-0-19-860742-7.
- Dashboard, Humanities Division [8th May 2008]. *L^AT_EX—Humanities Computing*. URL: <https://coral.uchicago.edu:8443/display/humcomp/LaTeX>.
- Dearborn, Elizabeth [2006]. “T_EX and Medicine”. In: *PracT_EX Journal* 4. URL: <http://tug.org/pracjourn/2006-4/dearborn>.
- Eijkhout, V. [2007]. *T_EX by Topic, A T_EXnician’s Reference*. Addison–Wesley. ISBN: 0-201-56882-9. URL: <http://www.eijkhout.net/tbt/>.
- Felici, James W. [2012]. *The Complete Manual of Typography A Guide to Setting Complete Type*. Second Edition. Adobe Press. ISBN: 978-0-321-77326-5.
- Fenn, Jürgen [2006]. “Managing Citations and Your Bibliography with BIBT_EX”. In: *PracT_EX Journal* 4. URL: <http://www.tug.org/pracjourn/2006-4/fenn/>.
- Feuersänger, Christian [5th Aug. 2010a]. *Manual for Package PGFPLOTS*. Version 1.4.1.
- [5th Aug. 2010b]. *Manual for Package PGFPLOTSTABLE*. Version 1.4.1.
- Fine, Jonathan [1992]. “Some Basic Control Macros for T_EX”. In: *TUGboat* 13.1.
- Fiorio, Christophe [14th Dec. 2004]. *algorithm2e.sty—package for algorithms*. Version 3.3.
- Flynn, Peter [2007]. “Rolling your own Document Class: Using L^AT_EX to keep away from the Dark Side”. In: *TUGboat* 28.1. URL: <http://www.tug.org/TUGboat/Articles/tb28-1/tb88flynn.pdf>.
- Garcia, Aracele, and Arthur Buchsbaum [2010]. “About L^AT_EX tools that students of Logic should know”. In: *PracT_EX Journal* 1. In Portuguese. URL: <http://tug.org/pracjourn/2010-1/garcia>.
- Giacomelli, Roberto [12th July 2009]. *calctab Package*. Version 0.6.1.
- Goldberg, Jeffrey P., and H.-Martin Münch [1st Feb. 2011]. *The lastpage Package*. Version 1.2g.

- Goossens, M., S. Rahtz, and F. Mittelbach [1997]. *The L^AT_EX Graphics Companion: Illustrating documents with T_EX and PostScript*. Addison–Wesley. ISBN: 0-201-85469-4.
- Graham, R. L., Donald E. Knuth, and O. Patashnik [1989]. *Concrete Mathematics: A Foundation for Computer Science*. Addison-Wesley. ISBN: 0-201-14236-8.
- Hedrick, Charles [15th Jan. 2003]. *Guidelines for Typography in NBCS*. URL: <http://www.nbc.rutgers.edu/~hedrick/typography/typography.janson-syntax.107514.pdf>.
- Heinz, Carsten, and Brooks Moses [22nd Feb. 2007]. *The Listings Package*. Version 1.4.
- Heldoorn, Marcel [2nd Dec. 2007]. *The SIunits—package* Consistent application of SI Units. Version 1.36.
- Høgholm, Morten [28th July 2008]. *The breqn Package*. Version 0.98. ——— [17th Jan. 2011]. *The xfrac Package*. Version 0.3b.
- Høgholm, Morten et al. [12th Feb. 2011]. *The mattools Package*. Version 1.10.
- Kern, Uwe [21st Jan. 2007]. *Extending L^AT_EX's color facilities: xcolor*. Version 2.11.
- Knuth, Donald E. [1990]. *The T_EXbook*. Addison–Wesley. ISBN: 0-201-13447-0. URL: <http://www.ctan.org/tex-archive/systems/knuth/tex/>.
- Kohler, Eddie [2011]. *otftotfm Manual*. Version 2.90. URL: <http://www.lcdf.org/type/otftotfm.1.html>.
- Krab Thorub, Kresten, Frank Jensen, and Chris Rowley [22nd Aug. 2007]. *The calc Package*, Infix Notation Arithmetic in L^AT_EX.
- Lamport, Leslie [1994]. *L^AT_EX: A Document Preparation System*. Addison–Wesley. ISBN: 0-021-52983-1.
- L^AT_EX3 Project [12th Mar. 1999]. *L^AT_EX₂_ε for Class and Package Writers*. URL: <http://www.latex-project.org/guides/clsguide.pdf>.
- L^AT_EX3 Project [9th Feb. 2000]. *L^AT_EX₂_ε Font Selection*. URL: <http://www.latex-project.org/guides/fntguide.pdf>.
- Lehman, Philipp. *The bibl_{at}ex Package*. Version 1.5. ——— [2004]. *The Font Installation Guide* Using Postscript Fonts to their Full Potential in L^AT_EX. Version 2.14.
- Longborough, Brent [28th Aug. 2011]. *tagging.sty*. Version 1.0.
- Midtiby, Henrik Skov [21st Apr. 2011]. *The todonotes Package*.
- Miede, André [24th Jan. 2010]. *The Classic Thesis Style*.
- Mittelbach, Frank, Robin Fairbairns, and Werner Lemberg [6th Jan. 2006]. *L^AT_EX Font Encodings*.
- Mühlich, Matthias [23rd Feb. 2006]. *The CoverPage Package*. Version 1.01.
- Oberdiek, Heiko [23rd Dec. 2010]. *The keyvalue Package*. Version 3.10.
- Ochsenmeier, Erwin [2011]. *FourSenses.net*. At the moment of writing, this site is being moved from <http://theotex.blogspot.com/>. URL: <http://en.foursenses.net/>.
- Oetiker, Thomas [8th Sept. 2010]. *An Acronym Environment for L^AT_EX₂_ε*. Version 1.36.

- Oetiker, Tobias et al. [2007]. *The Not so Short Introduction to L^AT_EX₂ ϵ* . URL: <http://tobi.oetiker.ch/lshort/>.
- Owens, John D. [2006]. “The Installation and use of OpenType Fonts in L^AT_EX”. In: *TUGboat* 27.2, 112–119.
- Pakin, Scot [2005]. *The Comprehensive L^AT_EX Symbol List*. URL: <http://tug.ctan.org/info/symbols/comprehensive/symbols-letter.pdf>.
- Patieri, Lórenzo [2010]. *Customizing classicthesis with the arsclassica Package*.
- Peyton Jones, S., and J. Hughes [1999]. Haskell 98: A Non-strict, Purely Functional Language. <http://www.haskell.org/onlinereport/>.
- Peyton Jones, Simon L., John Huges, and John Launchberry [1993]. “How to Give a Good Research Talk”. In: *ACM SIGPLAN Notices* 28.11, 9–12. URL: <http://research.microsoft.com/en-us/um/people/simonpj/papers/giving-a-talk/giving-a-talk.htm>.
- Rahts, Sebastian [1993]. “Essential NFSS2, Version 2”. In: *TUGboat* 14.2, 132–137.
- Reckdahl, Keith [2006]. *Using Imported Graphics in L^AT_EX and pdfL^AT_EX*. URL: <ftp://ftp.tex.ac.uk/tex-archive/info/epslatex.pdf>.
- Reichert, Axel [4th Aug. 1998]. *units.sty—nicefrac.sty*. Version 0.9b.
- Robertson, Will [26th Feb. 2011]. *The fontspec Package*. Version 2.1f.
- Scharrer, Martin [2011-07-23]. *List of Internal L^AT_EX₂ ϵ Macros useful to Package Authors*. Version 0.4.
- Schlicht, R. [10th Jan. 2010]. *The microtype Class*. Version 2.4.
- Schneider, Tom [27th Apr. 2011]. *L^AT_EX Style and BIB_TE_X Bibliography Formats for Biologists: T_EX and L^AT_EX Resources*. URL: <http://www-lmb.ncifcrf.gov/~toms/latex.html>.
- Senthil, Kumar M. [2007]. “L^AT_EX Tools for Life Scientists (BioT_EX-niques?)” In: *PracT_EX Journal* 4. URL: <http://tug.org/pracjourn/2007-4/senthil>.
- Smith, Peter. *L^AT_EX for Logicians*. URL: <http://www.logicmatters.net/latex-for-logicians/>.
- Strunk, W., and E. B. White [2000]. *The Elements of Style*. Fourth Edition. Macmillan Publishing. ISBN: 0-205-30902-x.
- Talbot, Nicola [15th Nov. 2009]. *datatool v 1.01: Database and data manipulation*. Version 2.03.
- Tanksley, Charlie. *L^AT_EX: A Guide for Philosophers*. URL: <http://www.charlietanksley.net/latex/>.
- *PhilT_EX Forums A Place for Philosophers to Learn about L^AT_EX*. URL: <http://www.charlietanksley.net/philtex/forum/>.
- Tantau, Till [25th Oct. 2010]. *TikZ & PGF*. Version 2.00-cvs.
- Tantau, Till, Joseph Wright, and Vedran Miletic [12th July 2010]. *The BEAMER Class*. Version 3.10.
- Taraborelli, Dario [2010]. *The Beauty of L^AT_EX*. URL: <http://nitens.org/taraborelli/latex>.
- Team, JabRef Development. *JabRef*.
- Tellechea, Christian [8th Apr. 2011]. *spreadtab*. Version 0.3c.
- TWG-TDS [23rd June 2004]. *A Directory Structure for T_EX Files*. Version 1.1. URL: <http://tug.org/tds/tds.pdf>.

- Thomson, Paul A. [2008a]. “Clinical Trials Management on the Internet—I. Using L^AT_EX and SAS to Produce Customized Forms”. In: *PracT_EX Journal* 3.
- [2008b]. “Clinical Trials Management on the Internet—II. Using L^AT_EX, PostScript, and SAS to Produce Barcode Label sheets”. In: *PracT_EX Journal* 3. URL: <http://tug.org/pracjourn/2008-3/thompson2>.
- Toledo, Sivan [2000]. “Exploiting Rich Fonts”. In: *TUGboat* 21.2, 121–129.
- Trask, R. L. [1997]. *Penguin Guide to Punctuation*. Penguin Books. ISBN: 0-140-51366-3.
- Tufte, Edward R. [2001]. *The Visual Display of Quantitative Information*. Second Edition. Graphics Press LLC. ISBN: 978-0-9613921-4-7.
- Turabian, Kate L. [2007]. *A Manual for Writers of Research Papers, Theses, and Dissertations*. Seventh. University of Chicago Press. ISBN: 978-0-226-82337-9.
- Turner, Ken [1st Nov. 2010]. *BIBT_EX Style Examples*. URL: <http://www.cs.stir.ac.uk/~kjt/software/latex/showbst.html>.
- Unger, Gerard [2007]. *While You’re Reading*. Mark Batty Publisher. ISBN: 978-0-9762245-1-8.
- Van Oostrum, Piet [2nd Mar. 2004]. *Page Layout in L^AT_EX*.
- Veytsman, Boris, and Leila Akhmadeeva [2006]. “Drawing Medical Pedigree Trees with T_EX and PSTricks”. In: *PracT_EX Journal* 4. URL: <http://tug.org/pracjourn/2006-4/veytsman>.
- Voß, Herbert [2010]. *Math Mode*. URL: <ftp://cam.ctan.org/tex-archive/info/math/voss/mathmode/Mathmode.pdf>.
- Wilson, Peter [13th Feb. 2011]. *The fonttable Package*. Version 1.6b. Maintained by Will Robertson.
- Wilson, Peter, and Lars Madsen [6th Mar. 2011]. *The Memoir Class*.
- Wright, Joseph [1st May 2010]. *pgfopts—L^AT_EX Package Options with pgfkeys*. Version 2.0.
- [15th June 2011]. *siunitx—A Comprehensive (SI) units package*. Version 2.2i.
- Zeidler, Eberhard, ed. [1996]. *Oxford User’s Guide to Mathematics*. Typeset in L^AT_EX by Bruce Hunt. Oxford University Press. ISBN: 0-19-850763-1.

Acronyms and Abbreviations

AMS	American Mathematical Society
API	Application Programming Interface
APL	A Programming Language
CTAN	Comprehensive TeX Archive Network
DVD	Digital Versatile Disk
CD	Compact Disk
FAQ	Frequently Asked Question
GUI	Graphical User Interface
IDE	Integrated Development Environment
JVM	Java Virtual Machine
ISBN	International Standard Book Number
OS	Operating System
SI	Système International d'Unités/International System of Units
TDS	TeX Directory Structure
TUG	TeX Users Group
URL	Uniform Resource Locator
VM	Virtual Machine
WYSIWYG	What You See is What You Get

Indexes

L^AT_EX and T_EX Commands

`\'`, 44
`\(`, 216, 217
`\)`, 216, 217
`\+`, 64, 65
`\,`, 9, 10, 24, 45, 46, 49, 50, 82,
121, 125, 126, 150–157,
159–164, 173, 175, 176,
180–184
`\-`, 64, 65
`\.`, 44
`\:`, 184
`\;`, 184, 187, 190
`\=`, 44, 64, 65
`\>`, 64
`\[`, 150, 154, 155, 157, 159–164,
172, 175, 176, 180, 181,
183
`\^`, 44
`_`, 42
`\#`, 42
`\$`, 42
`\%`, 42
`\&`, 42
`\|`, 49, 50, 59, 64, 124–126, 149,
151–154, 161, 191
`\|*`, 50
`\↪`, 47, 54
`\{`, 42, 155
`\}`, 42
`\~`, 44
`\]`, 150, 154, 155, 157, 159–164,
172, 175, 176, 180, 181,
183
`\‘`, 44
`\AA`, 44
`\aa`, 44
`\abstract`, 12
`\ac`, 55
`\acp`, 55
`\acro`, 55
`\acute`, 174
`\addbibresource`, 25, 27
`\addcontentsline`, 14
`\addlegentry`, 131, 134, 135,
137, 139
`\addlinespace`, 61
`\addplot`, 131–140
`\addplot+`, 138
`\address`, 34
`\addtocategory`, 29
`\addtocounter`, 211, 212, 217
`\addtolength`, 214, 215, 217
`\AE`, 45
`\ae`, 45
`\aleph`, 168
`\alert`, 233
`\Alph`, 69
`\alph`, 69, 71, 72
`\alpha`, 148, 172
`\amalg`, 165
`\AND`, 216
`\and`, 11, 216
`\angle`, 168
`\appendix`, 15
`\approx`, 164, 166
`\approxseq`, 166
`\arabic`, 69
`\arccos`, 162
`\arcsin`, 162
`\arctan`, 162
`\arg`, 162
`\arraycolsep`, 63
`\arrayrulewidth`, 63
`\arraystretch`, 63
`\ast`, 165
`\asympt`, 166
`\author`, 8–11, 228
`\b`, 44
`\backepsilon`, 166
`\backmatter`, 14
`\backsim`, 166
`\backsimeq`, 166
`\backslash`, 41, 42, 158, 168
`\bar`, 173, 174
`\baselineskip`, 214, 251
`\because`, 166
`\begin`, 9, 11, 14, 16, 19, 24, 27,
28, 30, 34, 161, 209
`\begingroup`, 43
`\beta`, 32, 148, 164, 172

- `\between`, 166
- `\bfdefault`, 262
- `\bfseries`, 43, 53, 70, 193, 194, 251
- `\bibcloseparen`, 25
- `\bibliography`, 14, 23, 24
- `\bibliographystyle`, 21, 24
- `\bibname`, 14
- `\bibnamedash`, 25
- `\bibopenparen`, 25
- `\bigcap`, 160
- `\bigcirc`, 165
- `\bigcup`, 160
- `\bigl`, 173
- `\bigodot`, 160
- `\bigoplus`, 160
- `\bigotimes`, 160
- `\bigr`, 173
- `\bigsqcup`, 160
- `\bigtriangledown`, 165
- `\bigtriangleup`, 165
- `\biguplus`, 160
- `\bigvee`, 160
- `\bigwedge`, 160
- `\binom`, 147, 150, 161
- `\bmod`, 162, 187
- `\boldmc`, 126
- `\boldsymbol`, 165
- `\boolean`, 216
- `\bot`, 168
- `\bottomrule`, 61, 62, 122, 123, 125, 126
- `\bowtie`, 166
- `\Box`, 168
- `\breve`, 174
- `\bullet`, 165
- `\Bumpeq`, 166
- `\bumpeq`, 166
- `\c`, 44
- `\cap`, 165
- `\caption`, 75–78, 124, 125, 186, 187, 202
- `\Case`, 189
- `\cc`, 34
- `\cdot`, 165, 180
- `\cdot`, 180
- `\cdot`, 180
- `\centering`, 78
- `\cfrac`, 159
- `\chapter`, 13–15, 17, 19, 27, 28, 31
- `\chapter*`, 13, 14
- `\check`, 174
- `\chi`, 148
- `\circ`, 165
- `\circeq`, 166
- `\cite`, 3, 21, 22, 24, 42, 47
- `\Citeauthor`, 27
- `\citeauthor`, 26
- `\citetitle`, 26
- `\citeyear`, 26
- `\cleardoublepage`, 30
- `\clearpage`, 29, 30, 37
- `\cline`, 60, 63
- `\closing`, 34
- `\clubsuit`, 168
- `\cmidrule`, 61
- `\colon`, 176, 180
- `\colorlet`, 90
- `\cong`, 166
- `\coprod`, 160
- `\cos`, 162
- `\cosh`, 162
- `\cot`, 162
- `\coth`, 162
- `\csc`, 162
- `\csname`, 206, 207, 210
- `\cup`, 165
- `\curlyeqprec`, 166
- `\curlyeqsucc`, 166
- `\d`, 44
- `\dagger`, 165
- `\dashv`, 166
- `\date`, 9, 10, 228
- `\ddagger`, 165
- `\dotsc`, 174
- `\dots`, 174
- `\dots`, 174
- `\dots`, 180
- `\DeclareBibliographyCategory`, 29
- `\DeclareFontFamily`, 257, 258
- `\DeclareFontShape`, 257, 258
- `\DeclareGraphicsExtensions`, 79
- `\DeclareMathOperator`, 146, 171
- `\DeclareMathOperator*`, 171, 172

`\DeclareRobustCommand`, 202
`\DeclareTextFontCommand`, 265
`\def`, 205–209, 218
`\defbibheading`, 28
`\definecolor`, 89, 90
`\deg`, 162
`\Delta`, 148, 149
`\delta`, 148
`\depth`, 215
`\det`, 162
`\Diamond`, 168
`\diamond`, 165
`\diamondsuit`, 168
`\digamma`, 148
`\dim`, 162
`\displaystyle`, 160
`\div`, 165
`\do`, 217
`\documentclass`, 9, 10, 14, 24, 32–34, 228, 230
`\dot`, 174
`\doteq`, 166
`\doteqdot`, 166
`\dotsb`, 159, 175, 181
`\dotsc`, 181
`\dotsi`, 181
`\dotsintop`, 163
`\dotsm`, 181
`\dotso`, 181
`\doublerulesep`, 63
`\Downarrow`, 158, 167
`\downarrow`, 158, 167
`\draw`, 82–94, 96–103, 105, 107–109, 112–116, 140

`\edef`, 205, 206
`\eIf`, 188, 189
`\ell`, 168, 169
`\else`, 213, 224, 242
`\ElseIf`, 188
`\emph`, 48, 50, 56, 237, 270, 276, 290, 296
`\emptyset`, 168
`\encl`, 34
`\end`, 9, 11, 14, 16, 19, 24, 27, 28, 30, 34, 209
`\endash`, 24
`\endcsname`, 206, 207, 210
`\endfirsthead`, 125, 126

`\endfoot`, 126
`\endgroup`, 43
`\endhead`, 126
`\endlastfoot`, 126
`\endlatsfoot`, 126
`\epsilon`, 43, 148
`\eqcirc`, 166
`\eqnumtag`, 152
`\eqref`, 150
`\equal`, 216
`\equiv`, 162, 166
`\eta`, 148
`\eUlseIf`, 188
`\euro`, 62
`\exists`, 168
`\exp`, 162
`\expandafter`, 206, 207
`\extracolsep`, 62, 63

`\fallingdotseq`, 166
`\familydefault`, 262–264
`\fi`, 212, 213, 217, 218, 224, 242
`\fill`, 62, 63, 89, 95, 96, 113
`\filldraw`, 89, 95
`\fint`, 163
`\flat`, 168
`\fontencoding`, 249
`\fontfamily`, 249, 263
`\fontseries`, 249
`\fontshape`, 251
`\fontsize`, 251, 262, 263
`\fontspec`, 252
`\fonttable`, 259
`\footnote`, 49
`\footnotesize`, 51
`\For`, 190
`\forall`, 168
`\ForEach`, 190, 191
`\foreach`, 102, 113, 114
`\frac`, 116, 158, 159, 162, 164, 172
`\framesubtitle`, 228, 229, 237
`\frametitle`, 228, 229, 233, 237
`\frenchspacing`, 47
`\frenccspacing`, 54
`\frontmatter`, 14
`\frown`, 166

`\Gamma`, 148, 149
`\gamma`, 148

`\gcd`, 162
`\geq`, 166, 182, 183, 187
`\gg`, 166
`\graphicspath`, 79
`\grave`, 174

`\H`, 44
`\hat`, 167, 173, 174
`\hbar`, 168
`\heartsuit`, 168
`\hline`, 60, 63
`\hom`, 162
`\hookleftarrow`, 167
`\hookrightarrow`, 167
`\hphantom`, 57, 122, 184
`\hspace`, 62, 63
`\Huge`, 51
`\huge`, 51
`\hyphenation`, 65

`\i`, 44
`\idotsint`, 160, 163
`\If`, 188, 192
`\ifnotes`, 213
`\ifthenelse`, 215, 216
`\ifx`, 218
`\iiiint`, 160, 163
`\iiiintop`, 163
`\iiint`, 160, 163
`\iiintop`, 163
`\iint`, 160, 163
`\Im`, 168
`\imath`, 167, 168
`\in`, 157, 166, 183, 184
`\include`, 16, 30, 211
`\includegraphics`, 78
`\includegraphics`, 77–79, 219
`\includeonly`, 16
`\index`, 31, 32
`\inf`, 162
`\infty`, 152, 160, 168
`\input`, 16
`\int`, 160, 162, 163, 181
`\intertext`, 153
`\iota`, 148
`\isodd`, 216
`\isundefined`, 216
`\itdefault`, 262
`\item`, 67–72, 231–233, 237
`\itemindent`, 71

`\itemsep`, 71
`\itshape`, 53, 194, 251

`\j`, 44
`\jmath`, 167, 168
`\Join`, 166

`\kappa`, 148
`\ker`, 162
`\kill`, 64, 65
`\KwData`, 187
`\KwIn`, 187
`\KwOut`, 187
`\KwResult`, 187
`\KwRet`, 187

`\L`, 44
`\l`, 44
`\label`, 17, 19, 76, 125, 150, 152, 176, 208
`\labelenumi`, 68, 69
`\labelenumii`, 68
`\labelenumiii`, 68, 69
`\labelenumiv`, 68
`\labelitemi`, 67, 68
`\labelitemii`, 67
`\labelitemiii`, 67
`\labelitemiv`, 67, 68
`\labelsep`, 71
`\labelwidth`, 71
`\Lambda`, 149
`\lambda`, 148
`\landdownint`, 163
`\landupint`, 163
`\langle`, 157, 158, 173
`\LARGE`, 51
`\Large`, 51
`\large`, 51, 251
`\LaTeX`, 9–11, 21, 24, 207
`\lceil`, 158
`\ldotp`, 180
`\ldots`, 47, 157, 180, 181, 183
`\left`, 153–158, 163, 172, 173, 183, 184
`\Leftarrow`, 167
`\leftarrow`, 167, 187
`\leftharpoondown`, 167
`\leftharpoonup`, 167
`\leftmargin`, 71, 72
`\Leftrightarrow`, 167

`\leftrightharrow`, 167
`\leftroot`, 164
`\legend`, 77
`\lElse`, 189
`\lengthtest`, 216
`\leq`, 155, 157, 158, 161, 166
`\let`, 208
`\lfloor`, 158
`\lg`, 162
`\lhd`, 165
`\lim`, 146, 162
`\liminf`, 162
`\limsup`, 162
`\linespread`, 251
`\lipsum`, 199
`\listofalgorithms`, 186
`\listoffigures`, 30
`\listoflistings`, 192
`\listoftables`, 30
`\listparindent`, 71
`\ll`, 166
`\ln`, 162
`\LoadClass`, 242
`\LoadClassWithOptions`, 242
`\log`, 162
`\long`, 206
`\Longleftarrow`, 167
`\longleftarrow`, 167
`\Longleftrightharrow`, 167
`\longleftrightharrow`, 167
`\longmapsto`, 167
`\Longrightarrow`, 167
`\longrightarrow`, 167
`\lstinputlisting`, 192
`\lstset`, 193, 194
`\lVert`, 157, 158
`\lvert`, 157, 158, 172

`\mainmatter`, 14
`\makeatletter`, 207–209
`\makeatother`, 207–209
`\makeindex`, 31
`\MakeRobustCommand`, 202
`\maketitle`, 9, 11, 12, 14, 30, 228
`\mapsto`, 167, 173, 176
`\marginpar`, 37, 49
`\mathbb`, 146, 157, 176, 183, 184
`\mathbf`, 146, 165
`\mathcal`, 165

`\mathfrak`, 146
`\mathit`, 165
`\mathring`, 174
`\mathrm`, 163, 165, 171, 183
`\mathsf`, 165
`\mathtt`, 165
`\matrix`, 104, 106
`\max`, 162
`\mddefault`, 262
`\mdseries`, 53, 251
`\medspace`, 184
`\metre`, 183
`\mho`, 168
`\mid`, 166, 184
`\midrule`, 61, 62, 122, 123, 125,
126
`\min`, 162
`\mod`, 162
`\mode`, 230, 231
`\mode*`, 231
`\models`, 166
`\mp`, 165
`\mu`, 148
`\multicolumn`, 60, 62, 123, 126
`\multimap`, 166

`\n`, 114, 115
`\nabla`, 168
`\natural`, 168
`\nearrow`, 167
`\NeedsTeXFormat`, 240
`\neg`, 168
`\negmedspace`, 184
`\negthickspace`, 184
`\negthinspace`, 184
`\neq`, 166, 187
`\newboolean`, 215
`\newcolumntype`, 123, 124
`\newcommand`, 37, 126, 199–201,
203
`\newcommand*`, 200, 223, 224
`\newcounter`, 71, 72, 211, 212,
217
`\newenvironment`, 71, 72, 209,
210, 229
`\newif`, 212, 213, 224
`\newlength`, 214
`\newrefformat`, 19
`\newtheorem`, 146, 178, 179

`\newtheoremstyle`, 179
`\ni`, 166
`\nocite`, 22
`\node`, 100–103, 105, 139
`\nodepart`, 100, 101
`\noexpand`, 206
`\nonfrenchspacing`, 47
`\nonumber`, 151, 152
`\normalfont`, 53, 263
`\normalsize`, 51, 262, 263
`\NOT`, 216
`\not`, 216, 217
`\notag`, 151
`\notestruer`, 213
`\notin`, 166
`\nu`, 148
`\nwarrow`, 167

`\O`, 44
`\o`, 44, 148
`\odot`, 165
`\OE`, 45
`\oe`, 45
`\oiinttop`, 163
`\oint`, 160
`\ointclockwise`, 163
`\ointctrlockwise`, 163
`\ointop`, 163
`\Omega`, 149
`\omega`, 148
`\ominus`, 165
`\opening`, 34
`\oplus`, 165
`\OR`, 216
`\or`, 216
`\oslash`, 165
`\Other`, 190
`\otimes`, 165
`\overbrace`, 174
`\overleftarrow`, 174
`\overleftrightarrow`, 167, 174
`\overline`, 173, 174
`\overrightarrow`, 174

`\p`, 114, 115
`\pageref`, 17
`\paragraph`, 31
`\parallel`, 166
`\Parencite`, 27
`\parencite`, 26, 46

`\parindent`, 214
`\parsep`, 71
`\parskip`, 71, 214
`\part`, 31
`\partial`, 164, 168
`\partopsep`, 71
`\PassOptionsToClass`, 242
`\path`, 83–90, 94–96, 98, 100, 107, 113–115
`\pause`, 231, 232
`\per`, 183
`\perp`, 166
`\pgfkeys`, 221–224, 240, 241, 261
`\pgfmathparse`, 110
`\pgfplotsset`, 132
`\PgfProcessPackageOptions`, 241
`\phantom`, 57, 58, 184
`\Phi`, 149
`\phi`, 148
`\Pi`, 149
`\pi`, 148
`\pitchfork`, 166
`\pm`, 165
`\pmb`, 165
`\pmod`, 162
`\pod`, 162
`\Pr`, 162
`\prec`, 166
`\precapprox`, 166
`\preccurlyeq`, 166
`\preceq`, 166
`\precsim`, 166
`\prettyref`, 19
`\prime`, 168
`\printbibheading`, 28
`\printbibliography`, 27
`\printbibliography`, 26–29
`\printindex`, 31
`\ProcessPgfPackageOptions`, 240, 241, 262
`\ProcessPgfPackageOptions*`, 240
`\prod`, 160
`\propto`, 166
`\protect`, 76, 124, 202
`\provideboolean`, 215
`\ProvidesClass`, 240
`\ProvidesFile`, 257–259
`\ProvidesPackage`, 240
`\ps`, 34

`\Psi`, 149
`\psi`, 148

`\qedhere`, 180, 237
`\quadr`, 49, 50, 151, 156, 182–184
`\quad`, 182, 184

`\raggedleft`, 58
`\raggedright`, 58
`\rangle`, 157, 158, 173
`\ratio`, 217
`\rceil`, 158
`\Re`, 168
`\ref`, 17–19, 42, 150, 152, 176, 177, 193
`\refname`, 22
`\relay`, 209
`\renewcommand`, 22, 200, 201
`\renewcommand*`, 25, 67–69, 200, 223
`\renewenvironment`, 210
`\Repeat`, 191
`\RequirePackage`, 242, 259
`\RequirePackageWithOptions`, 242
`\rfloor`, 158
`\rhd`, 165
`\rho`, 148
`\right`, 153–158, 163, 172, 173, 183, 184
`\Rightarrow`, 167
`\rightarrow`, 167
`\rightharpoondown`, 167
`\rightharpoonup`, 167
`\rightleftharpoons`, 167
`\rightmargin`, 71, 72
`\risingdotseq`, 166
`\rmdefault`, 262
`\rmfamily`, 53, 251
`\Roman`, 69
`\roman`, 69
`\rule`, 25
`\rVert`, 157, 158
`\rvert`, 157, 158, 163, 172

`\scdefault`, 262
`\scriptsize`, 50, 51, 251
`\scshape`, 53
`\searrow`, 167
`\sec`, 162
`\secnumdepth`, 30, 31

`\second`, 183
`\section`, 9, 11, 13, 15, 31, 208
`\section*`, 13
`\selectfont`, 251
`\selectfont`, 251, 262, 263
`\selectlanguage`, 65
`\seriesdefault`, 262, 263
`\setboolean`, 215
`\setcounter`, 30, 211, 212, 217
`\setkeys`, 78, 79
`\SetKwInput`, 187
`\setlength`, 72, 214, 215, 217
`\setminus`, 165
`\setromanfont`, 251
`\settodepth`, 215
`\settoheight`, 215
`\settowidth`, 215
`\SetTracking`, 52
`\sfdefault`, 262
`\sffamily`, 53
`\shade`, 89
`\shadedraw`, 89
`\shapedefault`, 262, 263
`\sharp`, 168
`\shortintertext`, 153
`\shortmid`, 166
`\shortparallel`, 166
`\SI`, 183
`\Sigma`, 149
`\sigma`, 148
`\signature`, 34
`\sim`, 166
`\simeq`, 166
`\sin`, 146, 162
`\sinh`, 162
`\sisetup`, 183
`\sldefault`, 262
`\slshape`, 53
`\small`, 51
`\smallfrown`, 166
`\smallsmile`, 166
`\smile`, 166
`\space`, 25
`\spadesuit`, 168
`\spy`, 102
`\sqcap`, 165
`\sqcup`, 165
`\sqiint`, 163
`\sqint`, 163

`\sqrt`, 159, 164
`\sqsubset`, 166
`\sqsubseteq`, 166
`\sqsupset`, 166
`\sqsupseteq`, 166
`\squared`, 183
`\ss`, 45
`\star`, 165
`\stepcounter`, 211, 212
`\strut`, 138
`\subparagraph`, 31
`\subsection`, 31
`\subset`, 166
`\subseteq`, 166
`\substack`, 161
`\subsubsection`, 31
`\succ`, 166
`\succapprox`, 166
`\succcurlyeq`, 166
`\succeq`, 166
`\succsim`, 166
`\sum`, 147, 150, 152, 159–161, 183
`\sup`, 162
`\supset`, 166
`\supseteq`, 166
`\surd`, 168
`\swarrow`, 167
`\Switch`, 189, 190

`\t`, 44
`\tabcolsep`, 62, 63
`\tablename`, 126
`\tableofcontents`, 3, 14, 15, 30
`\tan`, 162
`\tanh`, 162
`\tau`, 148
`\tcc`, 191
`\tcp`, 189, 191
`\tcp*`, 191, 192
`\TeX`, 21, 26, 31, 54, 200, 207
`\texnormal`, 251
`\text`, 146, 154, 155, 161, 174, 175, 183
`\textasciicircum`, 42
`\textasciitilde`, 42
`\textbackslash`, 41, 42, 201
`\textbf`, 43, 48, 53, 62, 122, 123, 125, 126, 133, 135, 137, 139, 140, 251
`\textcite`, 26
`\textendash`, 46
`\textendash`, 46, 276, 296
`\textheight`, 214
`\textit`, 53, 251
`\textls`, 247
`\textmd`, 53
`\textnormal`, 53
`\textrm`, 53, 251
`\textsc`, 52, 53, 55, 135, 154, 187
`\textsf`, 53
`\textsl`, 53
`\textstyle`, 160
`\textsuperscript`, 248
`\texttt`, 32, 53, 86, 120, 122, 201
`\textup`, 53
`\textvisiblespace`, 10
`\textwidth`, 79, 140, 214
`\thanks`, 11
`\theoremstyle`, 178, 179
`\therefore`, 166
`\Theta`, 148, 149
`\theta`, 148
`\thetable`, 126
`\thickapprox`, 166
`\thicksim`, 166
`\thickspace`, 184
`\thinspace`, 184
`\tikz`, 82, 83, 87
`\tikzset`, 83, 104, 111, 112, 116
`\tikztonodes`, 116
`\tikztostart`, 116
`\tikztotarget`, 116
`\tilde`, 174
`\times`, 82, 154, 155, 165, 175, 182
`\tiny`, 51
`\title`, 9, 10, 228
`\titlepage`, 11
`\to`, 162, 172, 176, 180
`\tocdepth`, 30, 31
`\top`, 168
`\toprule`, 61, 62, 122, 123, 125, 126
`\topsep`, 71
`\triangle`, 168
`\triangleleft`, 165
`\triangleright`, 165
`\ttdefault`, 262

`\ttfamily`, 53, 193, 194
`\u`, 44
`\uCase`, 189, 190
`\uElseIf`, 188, 189
`\uIf`, 188, 189
`\underbar`, 174
`\underbrace`, 174, 175
`\underleftarrow`, 167, 174
`\underletrightarrow`, 167, 174
`\underline`, 174
`\underrightarrow`, 167, 174
`\unlhd`, 165
`\unrhd`, 165
`\Uparrow`, 158, 167
`\uparrow`, 158, 167
`\updefault`, 262
`\Updownarrow`, 158, 167
`\updownarrow`, 158, 167
`\uplus`, 165
`\uproot`, 164
`\upshape`, 53
`\Upsilon`, 149
`\upsilon`, 148
`\usecounter`, 71, 72
`\usepackage`, 9, 10, 19, 21, 24, 25, 27, 34, 35
`\usetheme`, 237
`\usetikzlibrary`, 94, 104, 109, 141
`\v`, 44
`\value`, 216
`\varDelta`, 148, 149
`\varepsilon`, 148
`\varGamma`, 148, 149
`\varkappa`, 148
`\varLambda`, 149
`\varoiint`, 163
`\varointclockwise`, 163
`\varointctrlockwise`, 163
`\varOmega`, 149
`\varPhi`, 149
`\varphi`, 148
`\varPi`, 149
`\varpi`, 148
`\varpropto`, 166
`\varPsi`, 149
`\varrho`, 148
`\varSigma`, 149
`\varsigma`, 148
`\varTheta`, 148, 149
`\vartheta`, 148
`\varUpsilon`, 149
`\varXi`, 149
`\Vdash`, 166
`\vDash`, 166
`\vdash`, 166
`\vdots`, 180
`\vec`, 174
`\vee`, 165
`\vert`, 156, 157
`\vline`, 60, 63
`\vphantom`, 57, 58, 156
`\Vvdash`, 166
`\wedge`, 165
`\While`, 187, 191
`\whiledo`, 216, 217
`\widehat`, 174
`\widetilde`, 173, 174
`\widthof`, 217
`\wp`, 168
`\wr`, 165
`\x`, 114, 115
`\xhookleftarrow`, 167, 168
`\xhookrightarrow`, 167, 168
`\Xi`, 149
`\xi`, 148
`\xLeftarrow`, 167, 168
`\xleftarrow`, 167
`\xleftharpoondown`, 167, 168
`\xleftharpoonup`, 167, 168
`\xLeftrightarrow`, 167, 168
`\xleftrightharpoonup`, 167, 168
`\xleftrightharpoons`, 167, 168
`\xmapsto`, 167, 168
`\xrightarrow`, 167, 168
`\xrightarrow`, 167
`\xrightharpoondown`, 167, 168
`\xrightharpoonup`, 167, 168
`\xrightleftharpoons`, 167, 168
`\xticklabels`, 134
`\y`, 114, 115
`\yticklabels`, 134
`\zeta`, 148

Environments

abstract, 11
 algorithm, 185, 186
 algorithm*, 186
 algorithm2e, 185, 187, 189, 190
 align, 149, 151–153
 align*, 149, 153, 156, 182
 aligned, 153, 154
 alignedat, 153
 array, 58, 59, 61, 63, 123, 172
 axis, 131–134, 138, 141

 Bmatrix, 173
 bmatrix, 172, 173

 cases, 155, 175
 center, 58

 description, 37, 69, 70
 document, 9, 11, 14, 16, 19, 24, 30,
 34, 200, 201, 204, 207,
 210, 213

 enumerate, 37, 68–70
 eqnarray, 154
 equation, 149–151
 equation*, 149–151, 154

 figure, 75, 76, 78, 186
 flushleft, 58, 59
 flushright, 58
 footnotesize, 51
 frame, 227, 228, 230, 231, 233
 function, 186
 function*, 186

 gather, 150, 151
 gathered, 153

 Huge, 51
 huge, 51

 itemize, 37, 67, 68

 LARGE, 51
 Large, 51
 large, 51
 letter, 33, 34
 list, 68, 70–72
 longtable, 125, 126

 lstlisting, 192
 lstlistings, 192

 matrix, 173

 normalsize, 51

 pgfplots, 129
 pmatrix, 172
 procedure, 186
 procedure*, 186
 proof, 146, 176, 179, 180

 quotation, 49
 quote, 49, 50

 refsection, 27, 28

 scope, 112
 scriptsize, 51
 sidewaysfigure, 125
 sidewaysstable, 125
 small, 51
 smallmatrix, 173
 split, 150, 151
 subarray, 161

 tabbing, 58, 64, 65, 172, 185
 table, 124, 125, 186
 table*, 125
 tabular, 36, 58–61, 63, 123–125,
 127
 tabular*, 58, 59, 61, 63
 tikzpicture, 81–85, 89, 90, 102,
 103, 107

 tiny, 51
 titlepage, 11
 tt, 65

 verse, 49, 50
 Vmatrix, 173
 vmatrix, 173

Classes

amscs, 145

article, 3, 10, 11, 22, 24, 30, 33,
198, 200, 204, 239, 241–
243

beamer, xxvii, 81, 198, 199, 227,
228, 230–232, 239, 241,
242

book, 14, 30, 33

letter, 13, 33, 34

memoir, 35

report, 33

Packages

acronym, 55
 algorithm2e, 185–187, 189–191
 amsbsy, 146
 amscd, 146
 amsfonts, 146
 amsmath, 145, 146, 149, 150, 153,
 154, 158–160, 162–164,
 166, 171, 172, 179, 181
 amsopn, 146
 amssymb, 146
 amstext, 146
 amsthm, 146, 176–179
 arrows, 93, 94
 arsclassica, 35

 babel, 65
 beamerarticle, 229, 242, 243
 biblatex, vii, 25–29
 bidi, 65
 booktabs, 61, 125
 breqn, 182

 calc, 109, 217
 calctab, 127, 199
 ccaption, 77
 circuits.logic.CDH, 103
 circuits.logic.IEC, 103
 circuits.logic.US, 103
 classicthesis, 35
 colortbl, 61
 cool, xi, 172
 coverpage, 35
 csvpie, 131

 datatool, 127
 dcolumn, 122, 123
 dpfloat, 76

 enumerate, 69, 70
 esint, 163

 fancyhdr, 35
 fontenc, 259
 fontspec, 4, 245, 251, 254
 fonttable, 259
 fourier, 35

 graphicx, 77, 78

 hyperref, 36

 ifthen, 215–217

 keyval, 78, 219

 lastpage, 35
 lipsum, 198
 listings, 192, 193
 longtable, 125

 makerobust, 202
 mathastext, 342
 mathdesign, 35
 mathptmx, 9, 10
 mathtools, 35, 153
 microtype, 52, 247
 multind, 31

 named, 21, 24
 nicefrac, 248

 pgf, 81, 241
 pgfkeys, 111, 219, 220, 240, 241,
 246, 259, 261, 262
 pgfopts, 220, 240, 259, 262
 pgfplot, 141
 pgfplots, 75, 131, 132, 134, 136,
 137, 141
 pgfplotstable, 127
 polyglossia, 65
 prettyref, 18, 19, 150

 rotating, 125

 siunitx, 57, 122, 124, 183
 spreadtab, 127

 tagging, 213
 tikz, xxvii, 75, 81, 82, 84, 89, 99,
 101, 102, 107–109, 111,
 227, 232
 todonotes, 35

 url, 35

 xcolor, 89, 90
 xfrac, 248

Languages and External Commands

ANSI C, 192
ANSI C++, 192
apt-get, 285

bibtex, 3, 23, 24, 27, 31, 271, 272,
275, 290–292, 294

cd, 221
cfftotl, 252, 253

dvi_{pdf}, 7
dvi_{ps}, 7

eclipse, 4, 5
Eiffel, 192
emacs, 5, 7
Excel, 129
export, 287

gnuplot, 77

HTML, 192

ispell, 4, 66

Java, 192
java, 295

kathsea, 281, 300
kpathsea, 279–282, 298, 300–302
kpsewhich, 259

latex, 6–8, 12, 15, 16, 18, 23, 287
latexmk, 275, 294, 295

makeindex, 31, 275, 294
matlab, 131

otfinfo, 246, 254
otftotfm, 250, 254, 256, 257, 262

pdflatex, 3, 6–8, 245, 269, 271,
272, 275, 279–282, 287,
289–292, 294, 298, 300,
302
pdftex, 254
PHP, 192
Python, 192

tltestpage, 252, 253

texdoc, 27, 35
texhash, 282, 302
tlmgr, 267, 269, 278, 280–282,
285, 289, 296, 299, 301

ubuntu, 285
unix, 4, 252

vim, 5, 7, 16

xdvi, 7
XML, 192

Environment Variables

INFOPATH

 Unix, 287

MANPATH

 Unix, 287

PATH

 Unix, 287, 293

 Windows, 273

TEXDIR

 Unix, 287

TEXMFDBS

 Unix, 300

 Windows, 280

Colophon

THIS BOOK was created with pdf_lat_ex in a standard T_EX Live installation. The cover, the spine, and pages i–iv were produced by the publisher. The main text was typeset with the book class, using *FF Nexus* at 11/13×27 as the font family, and scaling its typewriter fonts to 83%.

The page, figure, and table layout were implemented with a user-defined package. The same holds for the `itemize`, `enumerate`, and `description` environments.

I had two main concerns when designing the page layout. First, I wanted figures and tables that could run into the margins. With program listings this is almost always needed; also this would let me typeset input and output side by side. My second concern was that I wanted the figure and table captions to the side. That way, long explanations would not be so disruptive.

The artwork at the back of the part titlepages is included courtesy of Billy Foley, a Cork-based artist and member of the Cork Artists Collective. The landscape on page 2 is included courtesy of the University College Cork Art Collection. More of Billy Foley's work may be found on www.billyfoley.com.

The `amsmath` and `amssymb` packages were used to help typeset the mathematics. The `mathastext` package was used with the option `italic` to make sure that the numbers and letters in mathematical expressions were typeset in *Nexus*. The result is not always perfect but overall it looks pleasing. The bibliography was typeset with the `biblatex` package. The `microtype` package was used with the options `tracking=smallcaps`, `expansion=true`, and `protrusion=true`.